

The `fibnum` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.1

Abstract

The package `fibnum` provides expandable fibonacci numbers for both L^AT_EX and plain T_EX.

Contents

1 Documentation	1
2 Implementation	3
2.1 Identification	3
2.2 Package resources	5
2.3 Setup precalculated values	5
2.4 Macros for precalculating values	6
2.5 Expandable calculations	7
3 Test	8
3.1 Catcode checks for loading	8
3.2 Test calculations	10
4 Installation	12
4.1 Download	12
4.2 Bundle installation	12
4.3 Package installation	12
4.4 Refresh file name databases	13
4.5 Some details for the interested	13
5 References	13
6 History	13
[2012/04/08 v1.0]	13
[2016/05/16 v1.1]	13
7 Index	14

1 Documentation

In the mailing list `texhax` Jan Abraham asked the question, how to get Fibonacci numbers in T_EX [1]:

Write a Macro in T_EX that compute the function `\fib{m}` All fibonacci numbers from 1 to m ($m < 40$).

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

This package provides an expandable implementation for the calculation of these numbers for a much larger set of indexes. For practical reasons the index is restricted to the same limitations that apply for TeX integer numbers. The range of the Fibonacci numbers, however, are not limited by the algorithm. They are only restricted to memory limitations, if they are hit.

The package is loaded as L^AT_EX package in L^AT_EX:

```
\usepackage{fibnum}
```

and as file in plain TeX:

```
\input fibnum.sty
```

The package does not know any options and it provides the macros `\fibnum` and `\fibnumPreCalc`.

`\fibnum {⟨index⟩}`

Macro `\fibnum` expects a TeX number as `⟨index⟩` in the official TeX number range from $-(2^{31}-1)$ up to $2^{31}-1$. In exact two expansion steps the macro expands to the Fibonacci number $F_{⟨index⟩}$. In case of a negative `⟨index⟩`, the “negafibonacci” number [2] is used. Formally the Fibonacci number F_n with integer index n , $n \in \mathbb{Z}$ and $n \in [-2\,147\,483\,647, 2\,147\,483\,647]$ that is returned by macro `\fibnum` with numerical argument n is defined the following way:

$$F_n = \begin{cases} 0 & \text{for } n = 0 \\ 1 & \text{for } n = 1 \\ F_{n-1} + F_{n-2} & \text{for } n > 1 \\ (-1)^{n+1} F_n & \text{for } n < 0 \end{cases} \quad (1)$$

Examples:

<code>\fibnum{-6}</code>	$\rightarrow -8$
<code>\fibnum{-5}</code>	$\rightarrow 5$
<code>\fibnum{-4}</code>	$\rightarrow -3$
<code>\fibnum{-3}</code>	$\rightarrow 2$
<code>\fibnum{-2}</code>	$\rightarrow -1$
<code>\fibnum{-1}</code>	$\rightarrow 1$
<code>\fibnum{0}</code>	$\rightarrow 0$
<code>\fibnum{1}</code>	$\rightarrow 1$
<code>\fibnum{2}</code>	$\rightarrow 1$
<code>\fibnum{3}</code>	$\rightarrow 2$
<code>\fibnum{4}</code>	$\rightarrow 3$
<code>\fibnum{5}</code>	$\rightarrow 5$
<code>\fibnum{6}</code>	$\rightarrow 8$
⋮	
<code>\fibnum{10}</code>	$\rightarrow 55$
⋮	
<code>\fibnum{46}</code>	$\rightarrow 1836311903$
⋮	
<code>\fibnum{100}</code>	$\rightarrow 354224848179261915075$
⋮	
<code>\fibnum{200}</code>	$\rightarrow 280571172992510140037611932413038677189525$
⋮	
<code>\fibnum{1000}</code>	$\rightarrow 434665576869374564356885276750406258025646$ $605173717804024817290895365554179490518904$ $038798400792551692959225930803226347752096$ $896232398733224711616429964409065331879382$ $98969649928516003704476137795166849228875$

```
\fibnumPreCalc {\langle index\rangle}
```

The package already provides precalculated Fibonacci numbers up to index 46. That means that calculations are not necessary for Fibonacci numbers that fit into the range of TeX numbers. Because macro `\fibnum` is expandable, it cannot store calculated Fibonacci numbers for later use. Macro definitions are forbidden in expandable contexts. If larger Fibonacci numbers are used more than once, than the compilation time can be shortened by calculating and storing the Fibonacci numbers beforehand. The argument $\langle index \rangle$ is a TeX number and macro `\fibnumPreCalc` ensures that the Fibonacci numbers F_0 up to $F_{\lfloor \langle index \rangle \rfloor}$ that are not already known are calculated and stored in internal macros. Internally only non-negative Fibonacci numbers are stored. If $\langle index \rangle$ is negative, then the needed positive Fibonacci numbers are calculated and stored. Example:

```
\fibnumPreCalc{50}
% calculates and stores the values for indexes 47..50.
% (Values for 0..46 are already stored by the package.)
\fibnum{49} % uses the stored value
\fibnum{51} % only calculates  $F_{51}$  from stored values  $F_{49}$  and  $F_{50}$ 
\fibnumPreCalc{100}
% calculates and stores the values for indexes 51..100
\fibnum{100} % uses the stored value for  $F_{100}$ 
\fibnum{-100} % uses the stored value for  $F_{100}$ 
%  $F_{-100} = -F_{100}$  according to equation (1).
```

2 Implementation

2.1 Identification

```
1 (*package)
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 %
7 \catcode44=12 %
8 \catcode45=12 %
9 \catcode46=12 %
10 \catcode58=12 %
11 \catcode64=11 %
12 \catcode123=1 %
13 \catcode125=2 %
14 \expandafter\let\expandafter\x\csname ver@fibnum.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17   \def\empty{}%
18   \ifx\x\empty % LaTeX, first loading,
19     % variable is initialized, but \ProvidesPackage not yet seen
20   \else
21     \expandafter\ifx\x\csname PackageInfo\endcsname\relax
22       \def\x#1#2{%
23         \immediate\write-1{Package #1 Info: #2.}%
24       }%
25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28   \x{fibnum}{The package is already loaded}%
29   \aftergroup\endinput
30 \fi
```

```

31 \fi
32 \endgroup%
Package identification:
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 %
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52   \immediate\write-1{Package: #3 #4}%
53   \xdef#1[#4]%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57   #2[#3]%
58   \ifx#1\@undefined
59     \xdef#1[#3]%
60   \fi
61   \ifx#1\relax
62     \xdef#1[#3]%
63   \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@fibnum.sty\endcsname
67 \ProvidesPackage{fibnum}%
68 [2016/05/16 v1.1 Fibonacci numbers (HO)]%
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname FibNum@\AtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @

```

```

92 \catcode123=1 %
93 \catcode125=2 %
94 \def\TMP@EnsureCode#1#2{%
95   \edef\FibNum@AtEnd{%
96     \FibNum@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}%
102 %\TMP@EnsureCode{36}{3}%
103 %\TMP@EnsureCode{38}{4}%
104 \TMP@EnsureCode{40}{12}%
105 \TMP@EnsureCode{41}{12}%
106 \TMP@EnsureCode{45}{12}%
107 \TMP@EnsureCode{46}{12}%
108 \TMP@EnsureCode{47}{12}%
109 \TMP@EnsureCode{58}{12}%
110 \TMP@EnsureCode{60}{12}%
111 \TMP@EnsureCode{62}{12}%
112 \TMP@EnsureCode{91}{12}%
113 %\TMP@EnsureCode{96}{12}%
114 \TMP@EnsureCode{93}{12}%
115 %\TMP@EnsureCode{94}{12}%
116 %\TMP@EnsureCode{124}{12}%
117 \edef\FibNum@AtEnd{\FibNum@AtEnd\noexpand\endinput}

```

2.2 Package resources

```

118 \begingroup\expandafter\expandafter\expandafter\endgroup
119 \expandafter\ifx\csname RequirePackage\endcsname\relax
120   \def\TMP@RequirePackage#1[#2]{%
121     \begingroup\expandafter\expandafter\expandafter\endgroup
122     \expandafter\ifx\csname ver@#1.sty\endcsname\relax
123       \input #1.sty\relax
124     \fi
125   }%
126   \TMP@RequirePackage{ltxcmds}[2011/04/18]%
127   \TMP@RequirePackage{intcalc}[2007/09/27]%
128   \TMP@RequirePackage{bigintcalc}[2007/11/11]%
129 \else
130   \RequirePackage{ltxcmds}[2011/04/18]%
131   \RequirePackage{intcalc}[2007/09/27]%
132   \RequirePackage{bigintcalc}[2007/11/11]%
133 \fi

```

2.3 Setup precalculated values

```

134 \def\FibNum@temp#1{%
135   \expandafter\def\csname FibNum@#1\endcsname
136 }
137 \catcode46=9 %
138 % dots are ignored
139 \FibNum@temp{0}{0}
140 \FibNum@temp{1}{1}
141 \FibNum@temp{2}{1}
142 \FibNum@temp{3}{2}
143 \FibNum@temp{4}{3}
144 \FibNum@temp{5}{5}
145 \FibNum@temp{6}{8}
146 \FibNum@temp{7}{13}
147 \FibNum@temp{8}{21}
148 \FibNum@temp{9}{34}
149 \FibNum@temp{10}{55}
150 \FibNum@temp{11}{89}

```

```

150 \FibNum@temp{12}{144}
151 \FibNum@temp{13}{233}
152 \FibNum@temp{14}{377}
153 \FibNum@temp{15}{610}
154 \FibNum@temp{16}{987}
155 \FibNum@temp{17}{1.597}
156 \FibNum@temp{18}{2.584}
157 \FibNum@temp{19}{4.181}
158 \FibNum@temp{20}{6.765}
159 \FibNum@temp{21}{10.946}
160 \FibNum@temp{22}{17.711}
161 \FibNum@temp{23}{28.657}
162 \FibNum@temp{24}{46.368}
163 \FibNum@temp{25}{75.025}
164 \FibNum@temp{26}{121.393}
165 \FibNum@temp{27}{196.418}
166 \FibNum@temp{28}{317.811}
167 \FibNum@temp{29}{514.229}
168 \FibNum@temp{30}{832.040}
169 \FibNum@temp{31}{1.346.269}
170 \FibNum@temp{32}{2.178.309}
171 \FibNum@temp{33}{3.524.578}
172 \FibNum@temp{34}{5.702.887}
173 \FibNum@temp{35}{9.227.465}
174 \FibNum@temp{36}{14.930.352}
175 \FibNum@temp{37}{24.157.817}
176 \FibNum@temp{38}{39.088.169}
177 \FibNum@temp{39}{63.245.986}
178 \FibNum@temp{40}{102.334.155}
179 \FibNum@temp{41}{165.580.141}
180 \FibNum@temp{42}{267.914.296}
181 \FibNum@temp{43}{433.494.437}
182 \FibNum@temp{44}{701.408.733}
183 \FibNum@temp{45}{1.134.903.170}
184 \FibNum@temp{46}{1.836.311.903}

\FibNum@max
185 \def\FibNum@max{46}

```

2.4 Macros for precalculating values

```

\fibnumPreCalc
186 \def\fibnumPreCalc#1{%
187   \expandafter\expandafter\expandafter
188   \FibNum@PreCalc\intcalcNum{#1}%
189 }

\FibNum@PreCalc
190 \def\FibNum@PreCalc#1{%
191   \ifnum#1<\ltx@zero
192     \expandafter\FibNum@PreCalc\ltx@gobble#1%
193   \else
194     \ifnum#1>\FibNum@max
195       \begingroup
196         \ltx@LocDimenA=#1sp\relax
197         \countdef\FibNum@i=255\relax
198         \FibNum@i=\FibNum@max\relax
199         \edef\FibNum@temp{%
200           \csname FibNum@\the\FibNum@i\endcsname%
201         }%
202         \advance\FibNum@i by -1\relax
203         \edef\FibNum@temp{%

```

```

204      \FibNum@temp
205      \csname FibNum@\the\FibNum@i\endcsname
206    }%
207    \advance\FibNum@i\ltx@two
208    \iftrue
209      \expandafter\FibNum@PreCalcAux\FibNum@temp
210    \fi
211  \endgroup
212 \fi
213 \fi
214 }

\FibNum@PreCalcAux
215 \def\FibNum@PreCalcAux#1/#2\fi{%
216 \fi
217 \edef\FibNum@temp{\BigIntCalcAdd#1!#2!}%
218 \global\expandafter
219 \let\csname FibNum@\the\FibNum@i\endcsname\FibNum@temp
220 \ifnum\FibNum@i=\ltx@LocDimenA
221   \xdef\FibNum@max{\the\FibNum@i}%
222 \else
223   \advance\FibNum@i\ltx@one
224   \expandafter\FibNum@PreCalcAux\FibNum@temp/#1%
225 \fi
226 }

```

2.5 Expandable calculations

```

\fibnum
227 \def\fibnum#1{%
228   \romannumeral
229   \expandafter\expandafter\expandafter\FibNum@Do\intcalcNum{#1}/%
230 }

\FibNum@Do
231 \def\FibNum@Do#1{%
232   \ifnum#1<\ltx@zero
233     \FibNum@ReturnAfterElseFiFi{%
234       \ifodd#1 %
235         \expandafter\expandafter\expandafter\ltx@zero
236       \else
237         \expandafter\expandafter\expandafter\ltx@zero
238         \expandafter\expandafter\expandafter-%
239       \fi
240       \romannumeral
241       \expandafter\FibNum@Do\ltx@gobble#1/%
242     }%
243   \else
244     \ifnum\FibNum@max<#1 %
245       \ltx@ReturnAfterElseFi{%
246         \expandafter
247         \FibNum@ExpCalc\number\expandafter\IntCalcInc\FibNum@max!%
248         \expandafter\expandafter\expandafter/%
249         \csname FibNum@\FibNum@max
250         \expandafter\expandafter\expandafter\endcsname
251         \expandafter\expandafter\expandafter/%
252         \csname FibNum@\expandafter\IntCalcDec\FibNum@max!%
253         \endcsname/%
254         #1%
255       }%
256     \else
257       \expandafter\expandafter\expandafter\ltx@zero

```

```

258     \csname FibNum@#1\expandafter\expandafter\expandafter\endcsname
259     \fi
260     \fi
261 }

\FibNum@ReturnAfterElseFiFi
262 \def\FibNum@ReturnAfterElseFiFi#1\else#2\fi\fi{\fi#1}

\FibNum@ExpCalc
263 \def\FibNum@ExpCalc#1/#2/#3/#4\fi{%
264   \fi
265   \ifnum#1=#4 %
266     \ltx@ReturnAfterElseFi{%
267       \expandafter\expandafter\expandafter\ltx@zero
268       \BigIntCalcAdd#2!#3!%
269     }%
270   \else
271     \expandafter\FibNum@ExpCalc
272     \number\IntCalcInc#1%
273     \expandafter\expandafter\expandafter/%
274     \BigIntCalcAdd#2!#3!%
275     #2/#4%
276   \fi
277 }

278 \FibNum@AtEnd%
279 
```

3 Test

3.1 Catcode checks for loading

```

280 {*test1}
281 \catcode`\{=1 %
282 \catcode`\}=2 %
283 \catcode`\#=6 %
284 \catcode`\@=11 %
285 \expandafter\ifx\csname count@\endcsname\relax
286   \countdef{count}=255 %
287 \fi
288 \expandafter\ifx\csname @gobble\endcsname\relax
289   \long\def{@gobble#1}%
290 \fi
291 \expandafter\ifx\csname @firstofone\endcsname\relax
292   \long\def{@firstofone#1{#1}}%
293 \fi
294 \expandafter\ifx\csname loop\endcsname\relax
295   \expandafter{@firstofone
296 \else
297   \expandafter{@gobble
298 \fi
299 }%
300   \def{loop#1\repeat}%
301   \def{body{#1}}%
302   \iterate
303 }%
304 \def\iterate{%
305   \body
306   \let\next\iterate
307 \else
308   \let\next\relax

```

```

309   \fi
310   \next
311 }%
312 \let\repeat=\fi
313 }%
314 \def\RestoreCatcodes{%
315 \count@=0 %
316 \loop
317 \edef\RestoreCatcodes{%
318   \RestoreCatcodes
319   \catcode\the\count@=\the\catcode\count@\relax
320 }%
321 \ifnum\count@<255 %
322   \advance\count@ 1 %
323 \repeat
324
325 \def\RangeCatcodeInvalid#1#2{%
326   \count@=#1\relax
327   \loop
328   \catcode\count@=15 %
329   \ifnum\count@<#2\relax
330     \advance\count@ 1 %
331   \repeat
332 }
333 \def\RangeCatcodeCheck#1#2#3{%
334   \count@=#1\relax
335   \loop
336   \ifnum#3=\catcode\count@
337   \else
338     \errmessage{%
339       Character \the\count@\space
340       with wrong catcode \the\catcode\count@\space
341       instead of \number#3%
342     }%
343   \fi
344   \ifnum\count@<#2\relax
345     \advance\count@ 1 %
346   \repeat
347 }
348 \def\space{ }
349 \expandafter\ifx\csname LoadCommand\endcsname\relax
350 \def\LoadCommand{\input fibnum.sty\relax}%
351 \fi
352 \def\Test{%
353   \RangeCatcodeInvalid{0}{47}%
354   \RangeCatcodeInvalid{58}{64}%
355   \RangeCatcodeInvalid{91}{96}%
356   \RangeCatcodeInvalid{123}{255}%
357   \catcode`@=12 %
358   \catcode`\-=0 %
359   \catcode`\-=14 %
360   \LoadCommand
361   \RangeCatcodeCheck{0}{36}{15}%
362   \RangeCatcodeCheck{37}{37}{14}%
363   \RangeCatcodeCheck{38}{47}{15}%
364   \RangeCatcodeCheck{48}{57}{12}%
365   \RangeCatcodeCheck{58}{63}{15}%
366   \RangeCatcodeCheck{64}{64}{12}%
367   \RangeCatcodeCheck{65}{90}{11}%
368   \RangeCatcodeCheck{91}{91}{15}%
369   \RangeCatcodeCheck{92}{92}{0}%
370   \RangeCatcodeCheck{93}{96}{15}%

```

```

371 \RangeCatcodeCheck{97}{122}{11}%
372 \RangeCatcodeCheck{123}{255}{15}%
373 \RestoreCatcodes
374 }
375 \Test
376 \csname @@end\endcsname
377 \end
378 ⟨/test1⟩

```

3.2 Test calculations

```

379 {*test-calc}
380 \catcode`:=1 %
381 \catcode`\:=2 %
382 \catcode`\#=6 %
383 \catcode`\@=11 %
384 \begingroup\expandafter\expandafter\expandafter\endgroup
385 \expandafter\ifx\csname RequirePackage\endcsname\relax
386 \input fibnum.sty\relax
387 \else
388 \RequirePackage{fibnum}[2016/05/16]%
389 \fi
390 \def\TestSet{%
391 \test{0}{0}%
392 \test{1}{1}%
393 \test{2}{1}%
394 \test{3}{2}%
395 \test{4}{3}%
396 \test{5}{5}%
397 \test{6}{8}%
398 \test{7}{13}%
399 \test{8}{21}%
400 \test{9}{34}%
401 \test{10}{55}%
402 \test{11}{89}%
403 \test{12}{144}%
404 \test{13}{233}%
405 \test{14}{377}%
406 \test{15}{610}%
407 \test{16}{987}%
408 \test{17}{1597}%
409 \test{18}{2584}%
410 \test{19}{4181}%
411 \test{20}{6765}%
412 \test{21}{10946}%
413 \test{22}{17711}%
414 \test{23}{28657}%
415 \test{24}{46368}%
416 \test{25}{75025}%
417 \test{26}{121393}%
418 \test{27}{196418}%
419 \test{28}{317811}%
420 \test{29}{514229}%
421 \test{30}{832040}%
422 \test{31}{1346269}%
423 \test{32}{2178309}%
424 \test{33}{3524578}%
425 \test{34}{5702887}%
426 \test{35}{9227465}%
427 \test{36}{14930352}%
428 \test{37}{24157817}%
429 \test{38}{39088169}%
430 \test{39}{63245986}%

```

```

431 \test{40}{102334155}%
432 \test{41}{165580141}%
433 \test{42}{267914296}%
434 \test{43}{433494437}%
435 \test{44}{701408733}%
436 \test{45}{1134903170}%
437 \test{46}{1836311903}%
438 \test{47}{2971215073}%
439 \test{48}{4807526976}%
440 \test{49}{7778742049}%
441 \test{50}{12586269025}%
442 \test{51}{20365011074}%
443 \test{52}{32951280099}%
444 \test{53}{53316291173}%
445 \test{54}{86267571272}%
446 \test{55}{139583862445}%
447 \test{56}{225851433717}%
448 \test{57}{365435296162}%
449 \test{58}{591286729879}%
450 \test{59}{956722026041}%
451 \test{60}{1548008755920}%
452 \test{61}{2504730781961}%
453 \test{62}{4052739537881}%
454 \test{63}{6557470319842}%
455 \test{64}{10610209857723}%
456 \test{65}{17167680177565}%
457 \test{66}{27777890035288}%
458 \test{67}{44945570212853}%
459 \test{68}{72723460248141}%
460 \test{69}{117669030460994}%
461 \test{70}{190392490709135}%
462 \test{71}{308061521170129}%
463 \test{72}{498454011879264}%
464 \test{73}{806515533049393}%
465 }
466 \def\msg#1{\immediate\write16}
467 \def\test#1#2{%
468   \TestAux{#1}{#2}%
469   \ifnum#1=0 %
470   \else
471     \ifodd#1 %
472       \TestAux{-#1}{#2}%
473     \else
474       \TestAux{-#1}{-#2}%
475     \fi
476   \fi
477 }
478 \def\TestAux#1#2{%
479   \def\Expected{#2}%
480   \expandafter\expandafter\expandafter\def
481   \expandafter\expandafter\expandafter\Result
482   \expandafter\expandafter\expandafter{%
483     \fibnum{#1}%
484   }%
485   \ltx@onellevel@sanitize\Result
486   \ifx\Result\Expected
487     \msg{* #1: ok.}%
488   \else
489     \msg{! fib(#1) = #2}%
490     \errmessage{fib(#1) <> \Result}%
491   \fi
492 }

```

```

493 \TestSet
494 \setbox0=\hbox{%
495 \msg{* PreCalc{73}}%
496 \fibnumPreCalc{73}%
497 }
498 \ifdim\wd0=0pt
499 \else
500 \errmessage{Unwanted stuff in PreCalc}%
501 \fi
502 \TestSet
503 \csname @@end\endcsname\end
504 
```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/fibnum.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/fibnum.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex fibnum.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>fibnum.sty</code>	→ <code>tex/generic/oberdiek/fibnum.sty</code>
<code>fibnum.pdf</code>	→ <code>doc/latex/oberdiek/fibnum.pdf</code>
<code>test/fibnum-test1.tex</code>	→ <code>doc/latex/oberdiek/test/fibnum-test1.tex</code>
<code>test/fibnum-test-calc.tex</code>	→ <code>doc/latex/oberdiek/test/fibnum-test-calc.tex</code>
<code>fibnum.dtx</code>	→ <code>source/latex/oberdiek/fibnum.dtx</code>

¹<http://ctan.org/pkg/fibnum>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{fibnum.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex fibnum.dtx
bibtex fibnum.aux
makeindex -s gind.ist fibnum.idx
pdflatex fibnum.dtx
makeindex -s gind.ist fibnum.idx
pdflatex fibnum.dtx
```

5 References

- [1] Jan Abraham. *[texhax] Beginner in TEX MACRO to compute functions.* 2012-04-07. URL: <http://tug.org/pipermail/texhax/2012-April/019146.html> (visited on 2012-04-08).
- [2] Wikipedia contributors. *Fibonacci numbers*. Version 486266088. Wikipedia, The Free Encyclopedia. 2012-04-08. URL: http://en.wikipedia.org/w/index.php?title=Fibonacci_number&oldid=486266088 (visited on 2012-04-08).

6 History

[2012/04/08 v1.0]

- First version.

[2016/05/16 v1.1]

- Documentation updates.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\#	283, 382
\%	359
\@	284, 357, 383
\@firstofone	292, 295
\@gobble	289, 297
\@undefined	58
\\"	358
\{	281, 380
\}	282, 381
A	
\advance . . .	202, 207, 223, 322, 330, 345
\aftergroup	29
B	
\BigIntCalcAdd	217, 268, 274
\body	301, 305
C	
\catcode	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 137, 281, 282, 283, 284, 319, 328, 336, 340, 357, 358, 359, 380, 381, 382, 383
\count@	286, 315, 319, 321, 322, 326, 328, 329, 330, 334, 336, 339, 340, 344, 345
\countdef	197, 286
\csname	14, 21, 50, 66, 76, 119, 122, 135, 200, 205, 219, 249, 252, 258, 285, 288, 291, 294, 349, 376, 385, 503
E	
\empty	17, 18
\end	377, 503
\endcsname	14, 21, 50, 66, 76, 119, 122, 135, 200, 205, 219, 250, 253, 258, 285, 288, 291, 294, 349, 376, 385, 503
\endinput	29, 117
\endlinechar	4, 35, 71, 77, 89
\errmessage	338, 490, 500
\Expected	479, 486
F	
\fibnum	2, <u>227</u> , 483
\FibNum@AtEnd . . .	95, 96, 117, 278
\FibNum@Do	229, <u>231</u>
\FibNum@ExpCalc	247, <u>263</u>
\FibNum@i	197, 198, 200, 202, 205, 207, 219, 220, 221, 223
\FibNum@max	<u>185</u> , 194, 198, 221, 244, 247, 249, 252
\FibNum@PreCalc	188, <u>190</u>
\FibNum@PreCalcAux	209, <u>215</u>
\FibNum@ReturnAfterElseFiFi	233, <u>262</u>
\FibNum@temp 134, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 199, 203, 204, 209, 217, 219, 224
\fibnumPreCalc	<u>3</u> , <u>186</u> , 496
H	
\hbox	494
I	
\ifdim	498
\ifnum	191, 194, 220, 232, 244, 265, 321, 329, 336, 344, 469
\ifodd	234, 471
\iftrue	208
\ifx	15, 18, 21, 50, 58, 61, 119, 122, 285, 288, 291, 294, 349, 385, 486
\immediate	23, 52, 466
\input	123, 350, 386
\IntCalcDec	252
\IntCalcInc	247, 272
\intcalcNum	188, 229
\iterate	302, 304, 306
L	
\LoadCommand	350, 360
\loop	300, 316, 327, 335
\ltx@gobble	192, 241
\ltx@LocDimenA	196, 220
\ltx@One	223
\ltx@Onelevel@sanitize	485
\ltx@ReturnAfterElseFi	245, 266
\ltx@two	207
\ltx@zero	191, 232, 235, 237, 257, 267
M	
\msg	466, 487, 489, 495
N	
\next	306, 308, 310
\number	247, 272, 341
P	
\PackageInfo	26
\ProvidesPackage	19, 67

R	
\RangeCatcodeCheck	417, 418, 419, 420, 421, 422,
. 333, 361, 362, 363, 364, 365,	423, 424, 425, 426, 427, 428,
366, 367, 368, 369, 370, 371, 372	429, 430, 431, 432, 433, 434,
\RangeCatcodeInvalid	435, 436, 437, 438, 439, 440,
. 325, 353, 354, 355, 356	441, 442, 443, 444, 445, 446,
\repeat 300, 312, 323, 331, 346	447, 448, 449, 450, 451, 452,
\RequirePackage 130, 131, 132, 388	453, 454, 455, 456, 457, 458,
\RestoreCatcodes 314, 317, 318, 373	459, 460, 461, 462, 463, 464, 467
\Result 481, 485, 486, 490	\TestAux 468, 472, 474, 478
\romannumeral 228, 240	\TestSet 390, 493, 502
S	\the 77, 78, 79, 80, 81, 82, 83, 84,
\setbox 494	97, 200, 205, 219, 221, 319, 339, 340
\space 339, 340, 348	\TMP@EnsureCode 94, 101, 102, 103,
	104, 105, 106, 107, 108, 109,
T	110, 111, 112, 113, 114, 115, 116
\Test 352, 375	\TMP@RequirePackage 120, 126, 127, 128
W	
\test 391, 392,	\wd 498
393, 394, 395, 396, 397, 398,	\write 23, 52, 466
399, 400, 401, 402, 403, 404,	
405, 406, 407, 408, 409, 410,	X
411, 412, 413, 414, 415, 416,	\x 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87