

Section name references in L^AT_EX*

Sebastian Rahtz (deceased)
Heiko Oberdiek (maintainer)
<https://github.com/ho-tex/hyperref/issues>

2016/05/21

Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

README The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

ChangeLog This file records the version history (also available as text file).

Options This file provides a short option summary.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroTeX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

hyperref.dtx This is the source code documentation for `hyperref`.

backref.dtx “Back referencing from bibliographical citations”

 **nameref.dtx** “Section name references in L^AT_EX” (this file)

Contents

1	Introduction	2
2	History	2

*This file has version number v2.44, last revised 2016/05/21.

3	Implementation	2
3.1	\label stuff	3
3.2	Changes of section macros	5
3.2.1	Class beamer	7
3.2.2	Theorems	8
3.3	Referencing stuff	8
3.4	Usage and frontend	10
3.5	Package ifthen support	11
3.6	Compatibility with varioref	11
3.7	Support for package listings	14

1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L^AT_EX macros, so it is vulnerable to future changes.

2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;
SPQR CERN July 1994;
Last mod. Sept. 3th MG;
Sept. 19th SPQR;
April 11th 1995 SPQR (added section formatting hook);
April 14th 1995 SPQR (compatibility with hyperref);
June 22 1995 SPQR (removed typeout from Sectionformat);
September 22 1997 added varioref hacks by Corey Minyard;
September 28th changes by David Carlisle.
More recent changes are recorded in ChangeLog.

The versions before 2009/11/27 v2.32 did not expand the title strings (of \section, \caption, ...). Then the behaviour switched to expanding, because this allows to remove unwanted macros (\label, ...). Despite this method is used in package titleref and class memoir, the first feedbacks let me conclude that this is not robust enough. Therefore I wrote package gettitlestring that uses the non-expanding method as default. It also allows me to use this package in package zref-titleref. See the package documentation of package gettitlestring how to change the method. It also provides a hook to remove additional unwanted macros, not supported by the package. Example:

```
\usepackage{gettitlestring}
\GetTitleStringDisableCommands{%
  \let\mylabel\@gobble
  \renewcommand\myindex[2]{}%
}
```

3 Implementation

```
1 (*package)
2 \RequirePackage{refcount}[2006/02/12]
3 \RequirePackage{gettitlestring}[2009/12/18]
4 \RequirePackage{ltxcmds}[2009/12/12]
```

We redefine `\label` so that it also writes the name of the current section to the `.aux` file; if the name ends in a dot, we zap it. To allow for the `hyperref` package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
\NR@strip@period
5 \def\NR@strip@period#1.\ltx@empty#2\@nil{#1}

\strip@period Macro \strip@period was removed in nameref 2012/07/28 v2.41 and reinserted in 2012/07/31 v2.42 for compatibility reasons with package subfig.
6 \def\strip@period#1.\relax#2\@@@{#1}

7 \def\NR@sanitize@labelname{%
8   \Conelevel@sanitize@\currentlabelname
9   \edef\@currentlabelname{%
10     \expandafter\NR@strip@period\@currentlabelname
11     \ltx@empty.\ltx@empty\@nil
12   }%
13 }
```

3.1 `\label` stuff

Here is tested, whether package `showkeys` is loaded. But if option `final` is used, the macros of `showkeys` are not defined, so we have to check an additional test.

```
\ifNR@showkeys
14 \newif\ifNR@showkeys
15 \NR@showkeysfalse
16 \@ifpackageloaded{showkeys}{%
17   \begingroup
18   \@ifundefined{SK@\label}{%
19     }{%
20     \global\NR@showkeystrue
21   }%
22   \endgroup
23 }{}

\label@hook
24 \providecommand*\label@hook{}%
25 \ltx@GlobalAppendToMacro{\label@hook}{%
26   \NR@sanitize@labelname
27 }

\label
28 \def\label#1{%
29   \bsphack
30   \begingroup
31   \def\label@name{#1}%
32   \label@hook
33   \protected@write\auxout{}{%
34     \string\newlabel{#1}{%
35       {\@currentlabel}%
36       {\thepage}%
37       {\@currentlabelname}%
38       {\@currentHref}%
39     }%
40   }%
```

```

41 \endgroup
42 \@esphack
43 }%
44 \ifNR@showkeys
45 \def\label#1{%
46   \@bsphack
47   \SK@\SK@\label{#1}%
48 \begingroup
49   \def\label@name{#1}%
50   \label@hook
51   \protected@write\auxout{}{%
52     \string\newlabel{#1}{%
53       {\@currentlabel}%
54       {\thepage}%
55       {\@currentlabelname}%
56       {\@currentHref}{}%
57     }%
58   }%
59 \endgroup
60 \@esphack
61 }%
62 \fi

```

```
\ltx@label
63 \let\ltx@label\label
```

Needed for the *subeqnarray* package.

```
\slabel
64 \@ifundefined{slabel}{}{%
65 \def\slabel#1{%
66   \@bsphack
67   \if@filesw
68     \begingroup
69       \def\label@name{#1}%
70       \label@hook
71       \let\thepage\relax
72       \def\protect{\noexpand\noexpand\noexpand}%
73       \edef@\tempa{%
74         \write\auxout{%
75           \string\newlabel{#1}{%
76             {\thesubequation}%
77             {\thepage}%
78             {\@currentlabelname}%
79             {\@currentHref}{}%
80           }%
81         }%
82       }%
83     \expandafter\endgroup
84     \atempa
85     \if@nobreak\ifvmode\nobreak\fi\fi
86   \fi
87   \@esphack
88 }%
89 }
```

Overload an AMS L^AT_EX command, which uses *\newlabel*. Sigh!

```

\@writetocindents@

90 \def\@writetocindents@{%
91  \begingroup
92  \@for\@tempa:=-1,0,1,2,3\do{%
93    \immediate\write\auxout{%
94      \string\newlabel{tocindent}\@tempa}{%
95      \csname r@tocindent\@tempa\endcsname{}{}{}{}%}
96    }%
97  }%
98 }%
99 \endgroup
100 }

```

3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks.

```

\NR@getttitle

101 \def\NR@getttitle#1{%
102  \GetTitleString{#1}%
103  \let\@currentlabelname\GetTitleStringResult
104 }

```

First the numbered sections. While we are about it, put in a useful section formatting macro.

```

\NR@sect

105 \let\NR@sect\@sect
106 \newcounter{section@level}

\@sect
107 \def\@sect#1#2#3#4#5#6[#7]#8{%
108  \setcounter{section@level}{#2}%
109  \NR@getttitle{#7}%
110  \NR@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{\Sectionformat{#8}{#2}}%
111 }

```

and now the unnumbered ones

```

\NR@ssect
112 \let\NR@ssect\@ssect

\NR@ssect
113 \def\@ssect#1#2#3#4#5{%
114  \NR@getttitle{#5}%
115  \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
116 }

```

Support for class memoir.

```

117 \ltx@ifundefined{ifheadnameref}{%
118 }{%
119  \ltx@ifundefined{M@sect}{%
120  }{%

```

```

121 \let\NRorg@M@sect\M@sect
122 \def\M@sect#1#2#3#4#5#6[#7][#8]{%
123   \ifheadnameref
124     \NR@gettitle{#8}%
125   \else
126     \NR@gettitle{#7}%
127   \fi
128   \NRorg@M@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}][{#8}]%
129 }%
130 }%
131 }

```

Parts and chapters are treated differently. sigh. `\@part` and `\@spart` are `\long` because of class memoir.

```

132 \let\NR@part\@part
133 \long\def\@part[#1]{%
134   \NR@gettitle{#1}%
135   \NR@part[{#1}]{#2}%
136 }
137 \let\NR@spart\@spart
138 \long\def\@spart[#1]{%
139   \NR@gettitle{#1}%
140   \NR@spart{#1}%
141 }
142 \let\NR@chapter\@chapter
143 \def\@chapter[#1]{%
144   \NR@gettitle{#1}%
145   \NR@chapter[{#1}]{#2}%
146 }
147 \ifclassloaded{memoir}{%
148   \ltx@ifUndefined{ifheadnameref}{%
149     }{%
150       \def\@chapter[#1]{%
151         \ltx@ifUndefined{ch@pt@c}{%
152           \NR@gettitle{#1}%
153         }{%
154           \ifx\ch@pt@c\ltx@empty
155             \NR@gettitle{#2}%
156           \else
157             \def\NR@temp{#1}%
158             \ifx\NR@temp\ltx@empty
159               \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
160             \else
161               \ifheadnameref
162                 \NR@gettitle{#1}%
163               \else
164                 \expandafter\NR@gettitle\expandafter{\ch@pt@c}%
165               \fi
166             \fi
167           \fi
168         }{%
169           \NR@chapter[{#1}]{#2}%
170         }{%
171       }{%
172     }{%
173   \let\NR@chapter\@chapter
174   \def\@chapter[#1]{%
175     \NR@gettitle{#1}%

```

```

176 \NR@schapter{#1}%
177 }

Captions

178 \AtBeginDocument{%
179   \c@ifpackagelloaded{hyperref}{%
180     \c@ifpackagelater{hyperref}{2009/12/05}\c@gobble\c@firstofone
181   }\c@firstofone
182   {%
183     \let\NR@@caption\@caption
184     \long\def\@caption#1[#2]{%
185       \NR@gettitle{#2}%
186       \NR@@caption{#1}{#2}%
187     }%
188   }%
189   \c@ifpackagelloaded{longtable}{%
190     \let\NRorg@LT@c@option\LT@c@ption
191     \def\LT@c@ption#1[#2]#3{%
192       \NRorg@LT@c@ption{#1}{#2}{#3}%
193       \def\@tempa{#2}%
194       \ifx\@tempa\@empty
195       \else
196         \NR@gettitle{#2}%
197       \fi
198     }%
199   }{}%

```

Environment ‘description’.

```

200 \ltx@IfUndefined{descriptionlabel}{%
201 }{%
202   \let\NRorg@descriptionlabel\descriptionlabel
203   \def\descriptionlabel#1{%
204     \NR@gettitle{#1}%
205     \NRorg@descriptionlabel{#1}%
206   }%
207 }%
208 }

```

Compatibility for package titlesec.

```

209 \AtBeginDocument{%
210   \c@ifpackagelloaded{titlesec}{%
211     \let\NRorg@ttl@sect@i\ttl@sect@i
212     \def\ttl@sect@i#1#2[#3]#4{%
213       \NR@gettitle{#4}%
214       \NRorg@ttl@sect@i{#1}{#2}{#3}{#4}%
215     }%
216   }{}%
217 }

```

3.2.1 Class beamer

```

218 \c@ifclassloaded{beamer}{%
219   \def\NR@PatchBeamer#1{%
220     \expandafter\let\csname NRorg@beamer@\#1\expandafter\endcsname
221     \csname beamer@\#1\endcsname
222     \begingroup
223     \edef\x{\endgroup
224       \long\def\expandafter\noexpand\csname beamer@\#1\endcsname

```

```

225      [####1]{% hash-ok
226      \noexpand\NR@getttitle{####1}%
227      \expandafter\noexpand\csname NRorg@beamer@#1\endcsname
228      [{####1}]%
229      }%
230      }%
231      \x
232      }%
233      \NR@PatchBeamer{section}%
234      \NR@PatchBeamer{subsection}%
235      \NR@PatchBeamer{subsubsection}%

```

Theorem names.

```

236  \addtobeamertemplate{theorem begin}{%
237      \expandafter\NR@getttitle\expandafter{\inserttheoremmaddition}%
238  }{}%
239  \c@ifdefinable{\NRorg@beamer@descriptionitem}{%
240      \let\NRorg@beamer@descriptionitem\beamer@descriptionitem
241      \renewcommand{\beamer@descriptionitem}[1]{%
242          \NR@getttitle{#1}%
243          \NRorg@beamer@descriptionitem{#1}%
244      }%
245  }%
246 }{}}

```

3.2.2 Theorems

```

247 \ltx@ifundefined{@opargbegintheorem}{}{%
248     \let\NRorg@opargbegintheorem\@opargbegintheorem
249     \def\@opargbegintheorem#1#2#3{%
250         \NR@getttitle{#3}%
251         \NRorg@opargbegintheorem{#1}{#2}{#3}%
252     }%
253 }
254 \AtBeginDocument{%
255     \c@ifpackageloaded{amsthm}{%
256         \let\NRorg@begintheorem\@begintheorem
257         \begingroup
258             \edef\x{\macro:\string#1\string#2[\string#3]}%
259             \c@onellevel@sanitize\x
260             \def\y#1->#2\@nil{#1}%
261             \edef\z{\expandafter\y\meaning\@begintheorem->\@nil}%
262             \c@onellevel@sanitize\z
263         \expandafter\endgroup
264         \ifx\x\z
265             \def\@begintheorem#1#2#3{%
266                 \NR@getttitle{#3}%
267                 \NRorg@begintheorem{#1}{#2}{#3}%
268             }%
269         \fi
270     }{}%
271 }

```

3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```

272 \providecommand*{\@currentlabelname}{}%
273 \providecommand*{\@currentHref}{}%

```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```
\@firstoffive
274 \long\def\@firstoffive#1#2#3#4#5{#1}

\@secondoffive
275 \long\def\@secondoffive#1#2#3#4#5{#2}

\@thirdoffive
276 \long\def\@thirdoffive#1#2#3#4#5{#3}

\@fourthoffive
277 \long\def\@fourthoffive#1#2#3#4#5{#4}

\@offive
278 \long\def\@fifthoffive#1#2#3#4#5{#5}

We have to redefine \ref and \pageref to know about extra reference elements.
Make them robust, and compatible with Babel. The Babel switch is mimicked if
not already defined. Some support for package showkeys is implemented. If option
notref of that package is set, \SK@ref has the meaning of \emptyset.

\@safe@activestru
279 \providecommand*\@safe@activestru{}%

\@safe@activesfa
280 \providecommand*\@safe@activesfa{}%

\NR@setref
281 \def\NR@setref#1{%
282   \begingroup
283     \@safe@activestru
284     \expandafter
285   \endgroup
286   \expandafter\NR@setref\csname r@#1\endcsname
287 }

\NR@setref
288 \def\NR@setref#1{%
289   \ifx\@undefined#1%
290     \let#1\relax
291   \fi
292   \@setref#1%
293 }

\T@ref
294 \def\T@ref#1{%
295   \NR@setref{\#1}\@firstoffive{\#1}%
296 }%

\T@pageref
297 \def\T@pageref#1{%
298   \NR@setref{\#1}\@secondoffive{\#1}%
299 }%
```

```

300 \ifNR@showkeys
301   \ifx\SK@ref\@empty
302   \else
303     \def\t@ref#1{%
304       \csname\@safe@activestrue
305       \SK@\SK@@ref{#1}%
306       \csname\@safe@activesfalse
307       \NR@setref{#1}\@firstoffive{#1}%
308     }%
309   \def\t@pageref#1{%
310     \csname\@safe@activestrue
311     \SK@\SK@@ref{#1}%
312     \csname\@safe@activesfalse
313     \NR@setref{#1}\@secondoffive{#1}%
314   }%
315 \fi
316 \fi

Package hyperref uses its own definitions of \ref and \pageref because it extends
the syntax by the star form. \DeclareRobustCommand is used by hyperref. Package
nameref can be loaded before, after hyperref or after hyperref's definitions in
\AtBeginDocument.

317 \@ifpackageloaded{hyperref}{%
318 }{%
319 \ref
320   \DeclareRobustCommand{\ref}{\t@ref}%
321 \pageref
322   \DeclareRobustCommand{\pageref}{\t@pageref}%
323 }

```

3.4 Usage and frontend

Access the (third) name part with \nameref;

```

\t@nameref
322 \def\t@nameref#1{%
323   \begingroup
324   \let\label\gobble
325   \NR@setref{#1}\@thirdoffive{#1}%
326   \endgroup
327 }%
328 \ifNR@showkeys
329   \ifx\SK@ref\@empty
330   \else
331     \def\t@nameref#1{%
332       \csname\@safe@activestrue
333       \SK@\SK@@ref{#1}%
334       \csname\@safe@activesfalse
335       \begingroup

```

```

336      \let\label\@gobble
337      \NR@setref{\#1}\@thirdoffive{\#1}%
338      \endgroup
339      }%
340  \fi
341 \fi

342 %\@ifclassloaded{memoir}{%
343 %  \ltx@ifundefined{@mem@titlerefno link}\ltx@secondoftwo{%
344 %    \ltx@ifundefined{@mem@titleref}\ltx@secondoftwo\ltx@firstoftwo
345 %  }%
346 %}\ltx@secondoftwo
347 %}%
348 % \DeclareRobustCommand*\nameref{%
349 %   \@ifstar\@mem@titlerefno link\@mem@titleref
350 % }%
351 %}%
352 \nameref
353 \DeclareRobustCommand*\nameref{%
354   \@ifstar\T@nameref\T@nameref
355 }%
356 \def\nameref#1{'\nameref{\#1}' on page-\pageref{\#1}}}

\Nameref An extended form which gives title and page number.
356 \def\nameref#1{'\nameref{\#1}' on page-\pageref{\#1}}


\Sectionformat The default for \Sectionformat
357 \providecommand\Sectionformat[2]{#1}

```

3.5 Package ifthen support

Package ifthen's \isodd does not work with \pageref because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in \ifthenelse in order to provide expandable versions without link of \ref and \pageref. As possible target I could only find \begin{group}:

```

358 \@ifpackageloaded{ifthen}{%
359   \let\NROrg@ifthenelse\ifthenelse
360   \def\ifthenelse{%
361     \let\begin{group}\NR@TE@begin{group}
362     \NROrg@ifthenelse
363   }%
364   \let\NROrg@begin{group}\begin{group}
365   \def\NR@TE@begin{group}{%
366     \let\begin{group}\NROrg@begin{group}
367     \begin{group}
368     \def\ref##1{\getrefbykeydefault{\##1}{}{??}}%
369     \def\pageref##1{\getrefbykeydefault{\##1}{page}{0}}%
370   }%
371 }%

```

3.6 Compatibility with varioref

[This section was derived by Corey Minyard minyard@acm.org from the varioref package]

```

372 \AtBeginDocument{%
373   \ifx\csname @@vpageref\endcsname\relax
374   \else
375     \def\@@vpageref#1[#2]{#3}{%
376       \begingroup
377         \csname @safe@activestruet\endcsname
378         \edef\x{\#3}%
379         \onelevel@sanitize\x
380         \toks@{%
381           \NR@@vpageref{#1}[{#2}]%
382         }%
383         \edef\x{\endgroup
384           \the\toks@\{\x\}%
385         }%
386         \x
387       }%
388     \def\NR@@vpageref#1[#2]{#3}{%
389       \leavevmode\unskip
390       \global\advance\c@vrcnt\@ne
391       \@ifundefined{r@\the\c@vrcnt\@vr}%
392         {\@namedef{r@\the\c@vrcnt\@vr}{{??}{??}{}}{}}{}}{%
393       \edef\@tempa{%
394         \expandafter\expandafter\expandafter
395         \csname r@\the\c@vrcnt\@vr\endcsname
396       }%
397       \@ifundefined{r@\the\c@vrcnt\@xvr}%
398         {\@namedef{r@\the\c@vrcnt\@xvr}{{??}{??}{}}{}}{%
399       \edef\@tempb{%
400         \expandafter\expandafter\expandafter
401         \csname r@\the\c@vrcnt\@xvr\endcsname
402       }%
403       {%
404         \let\@currentlabel\empty
405         \expandafter\label\expandafter{\the\c@vrcnt\@xvr}%
406       }%
407       \ifx\@tempa\@tempb
408       \else
409         \vref@err{%
410           \noexpand\vref at page boundary %
411           \@tempb-\@tempa\space (may loop)%
412         }%
413       \fi
414       \@ifundefined{r@#3}{\@namedef{r@#3}{{??}{??}{}}{}}{%
415       \edef\thevpagerefnum{%
416         \expandafter\expandafter\expandafter
417         \csname r@#3\endcsname
418       }%
419       \ifx\vref@space\@undefined
420         \space
421       \else
422         \vref@space
423       \fi
424       \ifx\@tempa\thevpagerefnum
425         #1%
426       \else
427         #2%
428       \is@pos@number\thevpagerefnum{%

```

```

429      \is@pos@number\@tempa{%
430          \tempcnta\@tempa
431          \advance\tempcnta\@ne
432      }%
433          \tempcnta\maxdimen
434      }%
435      \ifnum \thepagerefnum =\tempcnta
436          \ifodd\tempcnta
437              \if@twoside
438                  \reftextfaceafter
439              \else
440                  \reftextafter
441              \fi
442          \else
443              \reftextafter
444          \fi
445      \else
446          \advance\tempcnta-2 %
447          \ifnum \thepagerefnum =\tempcnta
448              \ifodd\tempcnta
449                  \reftextbefore
450              \else
451                  \if@twoside
452                      \reftextfacebefore
453                  \else
454                      \reftextbefore
455                  \fi
456              \fi
457          \else
458              \reftextfaraway{#3}%
459          \fi
460      \fi
461  }%
462      \reftextfaraway{#3}%
463  }%
464  \fi
465  {%
466      \let\currentlabel\empty
467      \expandafter\label\expandafter{\the\c@vrcnt \vr}%
468  }%
469  }%
470 \DeclareRobustCommand\vnameref[1]{%
471     \unskip~\nameref{#1}%
472     \vpageref[\unskip]{#1}%
473 }%
474 \fi
475 }

476 \@ifundefined{@Refstar}{%
477     \def\T@Ref#1{%
478         \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
479     }%
480     \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
481         \MakeUppercase{#1}%
482     }%
483 }%
484 \AtBeginDocument{%
485     \ifpackageloaded{varioref}{%

```

```
486  \c@ifundefined{\@Refstar}{%
487    \c@DeclareRobustCommand*\{\c@Ref\}[1]{%
488      \c@T\c@Ref{\#1}%
489    }%
490  }{}%
491 }{}%
492 }%
```

3.7 Support for package `listings`

```
493 \AtBeginDocument{%
494   \c@ifpackageloaded{listings}{%
495     \c@let\NROrg@\c@lst@MakeCaption\c@lst@MakeCaption
496     \c@def\c@lst@MakeCaption{%
497       \c@ifx\c@lst@label\c@empty
498       \c@else
499         \c@let\c@currentlabelname\c@lst@Caption
500       \c@fi
501       \c@NROrg@\c@lst@MakeCaption
502     }%
503   }{}%
504 }
```

```
505 </package>
```