

The `hycolor` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.8

Abstract

Package `hycolor` implements the color option stuff that is used by packages `hyperref` and `bookmark`. It is not intended as package for the user.

Contents

| | |
|---|-----------|
| 1 Documentation | 2 |
| 1.1 Summary | 2 |
| 2 Implementation | 3 |
| 2.1 Normalization | 3 |
| 2.1.1 Sanitize value of color option | 3 |
| 2.1.2 Normalize result | 4 |
| 2.2 Main algorithm for color options | 5 |
| 2.3 Package <code>bookmark</code> | 5 |
| 2.4 Utils | 7 |
| 2.5 Package <code>hyperref</code> | 8 |
| 2.5.1 Options Hyp.*color | 8 |
| 2.5.2 Generic algorithm | 10 |
| 2.5.3 Field options | 12 |
| 2.5.4 Detection for naked RGB values | 12 |
| 2.5.5 Options *bordercolor | 14 |
| 2.6 Package <code>attachfile2</code> | 15 |
| 2.7 Patch for package <code>xcolor</code> | 17 |
| 2.7.1 Fix fragile <code>\@frameb@x</code> | 20 |
| 3 Test | 20 |
| 3.1 Test for package <code>attachfile2</code> | 24 |
| 3.2 Test for package <code>xcolor</code> | 26 |
| 3.2.1 Test for <code>\@frameb@x/\fbox</code> | 27 |
| 4 Installation | 28 |
| 4.1 Download | 28 |
| 4.2 Bundle installation | 28 |
| 4.3 Package installation | 28 |
| 4.4 Refresh file name databases | 29 |
| 4.5 Some details for the interested | 29 |
| 5 Catalogue | 29 |

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

| | |
|-------------------|-----------|
| 6 History | 30 |
| [2007/04/09 v1.0] | 30 |
| [2007/04/11 v1.1] | 30 |
| [2008/07/29 v1.2] | 30 |
| [2008/08/01 v1.3] | 30 |
| [2008/09/08 v1.4] | 30 |
| [2009/10/02 v1.5] | 30 |
| [2009/12/12 v1.6] | 30 |
| [2011/01/30 v1.7] | 30 |
| [2016/05/16 v1.8] | 30 |
| 7 Index | 30 |

1 Documentation

The package `hycolor` implements color options for packages `hyperref` and `bookmark`.

Package `xcolor` provides macros for extracting color values and converting color data to other color models. If this package is loaded, the full range of color specifications of packages `color` and `xcolor` are supported including the optional argument for the color model.

```
\hypersetup{linkbordercolor=red} % needs xcolor
\hypersetup{linkbordercolor=[named]{red}} % needs xcolor
\hypersetup{linkbordercolor=[rgb]{1,0,0}}
```

Without package `xcolor` some of the options only support some models, if they are given directly, e.g.:

```
\bookmarksetup{color=[rgb]{1,0,0}}
```

Because of compatibility some options of `hyperref` also support space separated RGB values:

```
\hypersetup{linkbordercolor=1 0 0} % is the same as
\hypersetup{linkbordercolor=[rgb]{1,0,0}}
```

Coloring is optional, it can be turned off by using an empty value:

```
\hypersetup{linkbordercolor={}}
```

The PDF specification knows some kind of an empty color setting without values. This applies to form field colors. The new A virtual color model `empty` is introduced for this purpose, e.g.

```
\TextField[backgroundcolor={[empty]}, ...]{...} % or
\TextField[{backgroundcolor=[empty]}, ...]{...}
```

PDF specification 1.7 also allows this for border link colors. But this isn't currently supported by this package, because the tested viewers (AR7/Linux, `xpdf` 3.00, `ghostscript` 8.54) don't support this yet. In contrary `ghostscript` generates an error message.

1.1 Summary

| Color option | Models without xcolor | RGB color | Model empty |
|-------------------------------|------------------------------|-----------|-------------|
| <code>BKM.color</code> | <code>gray, rgb</code> | no | no |
| <code>Hyp.*color</code> | <code>all</code> | no | no |
| <code>Hyp.*bordercolor</code> | <code>gray, rgb</code> | yes | no |
| <code>Field.*color</code> | <code>gray, rgb, cmyk</code> | yes | yes |
| <code>AtFi.color</code> | <code>gray, rgb</code> | yes | no |

“RGB color” means that the color value can be given as space separated RGB numbers (real numbers in the range from 0 to 1). Explanation of the color option prefixes:

| Prefix | Explanation |
|--------|--|
| BKM | Package bookmark |
| Hyp | Package hyperref: package options or \hypersetup |
| Field | Package hyperref: Form field options |
| AtFi | Package attachfile2: option color |

2 Implementation

```

1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{hycolor}%
4 [2016/05/16 v1.8 Color options for hyperref/bookmark (HO)]%
5 \RequirePackage{xcolor-patch}[2016/05/16]

```

2.1 Normalization

2.1.1 Sanitize value of color option

Procedure DefSanitized(cmd, value)

Param: cmd (macro)

Param: value (value of color option)

Result: value is expanded, sanitized, and stored in macro cmd.

Initialize active characters;

cmd := Expand value;

Sanitize cmd;

Sanitization means that the string does not contain any macros or special tokens. It consists of characters with catcode 12 (other). The only exception is the space with catcode 10 (space).

\HyColor@DefSanitized

```

6 \begingroup
7 \catcode`!=13 %
8 \catcode`\:=13 %
9 \catcode`\-=13 %
10 \catcode`\+=13 %
11 \catcode`\;=13 %
12 \catcode`\"=13 %
13 \catcode`\>=13 %
14 \edef\x{%
15   \def\noexpand!{\string!}%
16   \def\noexpand:{\string:}%
17   \def\noexpand-{\string-}%
18   \def\noexpand+{\string+}%
19   \def\noexpand;{\string;}%
20   \def\noexpand"{\string"}%
21   \def\noexpand>{\string>}%
22 }%
23 \def\y#1{\endgroup
24 \def\HyColor@DefSanitized##1##2{%
25   \begingroup
26   \csname @safe@activestruce\endcsname
27   #1%
28   \edef\x{\endgroup
29   \def\noexpand##1##2{%
30     }%
31   \x

```

```

32      \@onellevel@sanitize##1%
33  }%
34 }%
35 \expandafter\y\expandafter{\x}

```

2.1.2 Normalize result

Procedure NormalizeNum(*value*, *cmd*)

Param: *value* (Sanitized explicit number)

Param: *cmd* (Macro that stores result)

Result: *cmd* contains normalized number

```

if value pt < 0pt then
|   cmd ← 0;
else if number before dot of value < 1 then
|   cmd ← number after dot of value;
|   cmd ← strip trailing zeros from cmd;
|   if dot remains only then
|   |   cmd ← 0;
|   end
|   else
|   |   cmd ← 1;
|   end

```

The number is limited to the range between 0.0 and 1.0 and formatted as short PDF number without leading or trailing zeros. The precision of the number isn't changed.

\HyColor@NormalizeNum

```

36 \def\HyColor@NormalizeNum#1#2{%
37   \ifdim#1pt<\z@
38     \def#2{0}%
39   \else
40     \edef#2{\zap@space#1 \@empty}%
41     \expandafter\HyColor@CheckDot#2..\@nil#2%
42   \fi
43 }
44 \def\HyColor@CheckDot#1.#2.#3\@nil#4{%
45   \ifnum0#1<\@ne
46     \ifx\\#2\\%
47       \def#4{0}%
48     \else
49       \edef#4{\HyColor@ReverseString#2\@nil{} }%
50       \edef#4{\expandafter\HyColor@StripLeadingZeros#4\@empty}%
51       \ifx#4\@empty
52         \def#4{0}%
53       \else
54         \edef#4{\expandafter\HyColor@ReverseString#4\@nil{} }%
55       \fi
56     \fi
57   \else
58     \def#4{1}%
59   \fi
60 }
61 \def\HyColor@ReverseString#1#2\@nil#3{%
62   \ifx\\#2\\%
63     #1#3%
64   \else
65     \@ReturnAfterFi{%
66       \HyColor@ReverseString#2\@nil{#1#3}%
67     }%

```

```

68 \fi
69 }
70 \long\def\@ReturnAfterFi#1\fi{\fi#1}
71 \def\HyColor@StripLeadingZeros#1{%
72   \ifx#10%
73     \expandafter\HyColor@StripLeadingZeros
74   \else
75     #1%
76   \fi
77 }

\HyColor@NormalizeCommaRGB

78 \def\HyColor@NormalizeCommaRGB#1,#2,#3\@nil#4{%
79   \HyColor@NormalizeNum{#1}\HyColor@temp
80   \let#4\HyColor@temp
81   \HyColor@NormalizeNum{#2}\HyColor@temp
82   \edef#4{\HyColor@temp}%
83   \HyColor@NormalizeNum{#3}\HyColor@temp
84   \edef#4{\HyColor@temp}%
85 }

\HyColor@NormalizeCommaCMYK

86 \def\HyColor@NormalizeCommaCMYK#1,#2,#3,#4\@nil#5{%
87   \HyColor@NormalizeNum{#1}\HyColor@temp
88   \let#5\HyColor@temp
89   \HyColor@NormalizeNum{#2}\HyColor@temp
90   \edef#5{\HyColor@temp}%
91   \HyColor@NormalizeNum{#3}\HyColor@temp
92   \edef#5{\HyColor@temp}%
93   \HyColor@NormalizeNum{#4}\HyColor@temp
94   \edef#5{\HyColor@temp}%
95 }

```

2.2 Main algorithm for color options

Procedure MainColorOptionAlgorithm(*key*, *value*, *cmd*)

Param: *key* (name of color option)

Param: *value* (value of color option)

Param: *cmd* (macro that stores result)

Result: Macro *cmd* contains the calculated color specification string or has the meaning of `\relax` if the color must not set

`DefSanitized(temp, value);`

`Call option specific algorithm(key, temp, cmd);`

2.3 Package bookmark

Since v0.8 2007/03/27 package `bookmark` only provides one color option `color`. Because option `rgbcolor` can easily given as color specification in model `rgb`:

`rgbcolor=<r> <g> ≡ color=[rgb]{<r>,<g>,}`

Package `bookmark` stores the result in macro `\BKM@color`. The empty string is

interpreted as *no color*.

Procedure BookmarkColor(*value*, *cmd*, *package*, *option*)

```

Param: value (value of option color)
Param: cmd (macro for result)
Param: package (package name for error message)
Param: option (option name for error message)

switch value do
  case empty do
    | cmd  $\leftarrow$  no color;
  end
  case with model do
    | if with xcolor then
    |   | cmd  $\leftarrow$  ConvertToRGB(model, values);
    | else
    |   | if model = rgb then
    |     |   | cmd  $\leftarrow$  values as normalized values;
    |   | else if model = gray then
    |     |   | cmd  $\leftarrow$  values as normalized tripled values;
    |   | else
    |     |   | error;
    |   | end
    | end
  end
  otherwise do
    | if with xcolor then
    |   | (model, values)  $\leftarrow$  get model and values;
    |   | cmd  $\leftarrow$  ConvertToRGB(model, values);
    | else
    |   | error;
    | end
  end
end
```

```

96 \def\HyColor@BookmarkColor#1#2#3#4{%
97   \HyColor@IfModel{#1}{%
98     \HyColor@IfXcolor{%
99       \convertcolorspec\HyColor@model\HyColor@values
100      \HyColor@model@rgb#2%
101      \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
102    }{%
103      \ifx\HyColor@model\HyColor@model@rgb
104        \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
105      \else
106        \ifx\HyColor@model\HyColor@model@gray
107          \expandafter\HyColor@NormalizeNum
108          \expandafter{\HyColor@values}#2%
109        \edef#2{#2 #2 #2}%
110      \else
111        \let#2\@empty
112        \HyColor@ModelErrorNoXcolor{#3}{#4}%
113      \fi
114    \fi
115  }{%
116    \let#2\HyColor@values
117    \ifx#2\@empty
118    \else
119      \HyColor@IfXcolor{%
```

```

121      \extractcolorspec{\#1}#2%
122      \expandafter\convertcolorspec#2\HyColor@model@rgb#2%
123      \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
124  }{%
125      \let#2\@empty
126      \HyColor@ErrorSpecNoXcolor{\#3}{\#4}%
127  }%
128  \fi
129 }%
130 }

131 \def\HyColor@ModelErrorNoXcolor#1#2{%
132   \PackageError{#1}{%
133     Color model '\HyColor@model' is not supported\MessageBreak
134     without package 'xcolor' in\MessageBreak
135     '#2=[\HyColor@model]{\HyColor@values}',%
136   }\@ehc
137 }

138 \def\HyColor@ErrorSpecNoXcolor#1#2{%
139   \PackageError{#1}{%
140     This color specification is not supported\MessageBreak
141     without package 'xcolor' in\MessageBreak
142     '#2=\HyColor@values'%
143   }\@ehc
144 }

145 \def\HyColor@IfModel#1{%
146   \@ifnextchar{%
147     \HyColor@WithModel
148   }{%
149     \HyColor@WithoutModel
150   }%
151   #1\@nil
152 }
153 \def\HyColor@WithModel[#1]#2\@nil{%
154   \HyColor@DefSanitized\HyColor@model{#1}%
155   \HyColor@DefSanitized\HyColor@values{#2}%
156   \@firstoftwo
157 }
158 \def\HyColor@WithoutModel#1\@nil{%
159   \let\HyColor@model\relax
160   \HyColor@DefSanitized\HyColor@values{#1}%
161   \@secondoftwo
162 }

```

2.4 Utils

```

\@ReturnAfterFi
163 \long\def\@ReturnAfterFi#1\fi{\fi#1}

\HyColor@IfXcolor
164 \def\HyColor@IfXcolor{%
165   \begingroup\expandafter\expandafter\expandafter\endgroup
166   \expandafter\ifx\csname convertcolorspec\endcsname\relax
167   \expandafter\@secondoftwo
168   \else
169   \expandafter\@firstoftwo
170   \fi
171 }

172 \def\HyColor@model@empty{empty}
173 \onelevel@sanitize\HyColor@model@empty
174 \def\HyColor@model@gray{gray}

```

```

175 \@onelvel@sanitize\HyColor@model@gray
176 \def\HyColor@model@rgb{rgb}
177 \@onelvel@sanitize\HyColor@model@rgb
178 \def\HyColor@model@cmyk{cmyk}
179 \@onelvel@sanitize\HyColor@model@cmyk
180 \def\HyColor@model@Gray{Gray}
181 \@onelvel@sanitize\HyColor@model@Gray

```

2.5 Package `hyperref`

2.5.1 Options `Hyp.*color`

```

182 \def\HyColor@UseColor#1{%
183   \ifx#1\relax
184   \else
185     \ifx#1\empty
186     \else
187       \expandafter\HyColor@@UseColor#1\@nil
188     \fi
189   \fi
190 }
191 \def\HyColor@@UseColor{%
192   \@ifnextchar[\HyColor@@@UseColor\HyColor@@@@UseColor
193 ]
194 \def\HyColor@@@UseColor[#1]#2\@nil{%
195   \color[{#1}]{#2}%
196 }
197 \def\HyColor@@@UseColor#1\@nil{%
198   \color{#1}%
199 }

```

Procedure `HyperrefColor(value, cmd)`

Param: *value* (value of the option)

Param: *cmd* (macro for result)

```

switch value do
  case empty do
    | cmd ← no color;
  end
  case with model do
    | Call \color with model;
  end
  case without model do
    | Call \color without model;
  end
end

```

```

200 \def\HyColor@HyperrefColor#1#2{%
201   \HyColor@IfModel{#1}{%
202     \edef#2{\{\HyColor@model\}\{\HyColor@values\}}%
203   }{%
204     \let#2\HyColor@values
205     \ifx#2\empty
206       \let#2\relax
207     \fi
208   }%
209 }

```


2.5.2 Generic algorithm

Procedure Algorithm X0134(value, cmd, package, option)

Param: *value* (value of the option)
Param: *cmd* (macro for result)
Param: *package* (package name for error message)
Param: *option* (option name for error message)

```

switch value do
  case empty do
    | cmd ← no color;
  end
  case with model do
    switch model do
      case empty do
        | cmd ← "";
      end
      case gray, rgb, cmyk do
        | cmd ← output();
      end
      case Gray do
        | if with xcolor then
          | (model, values) ← convert to gray;
        else
          | error(package, option, "Missing xcolor"), cmd ← no color;
        end
      end
      else
        | if with xcolor then
          | (model, values) ← convert to rgb;
          | cmd ← output();
        else
          | error(package, option, "Missing xcolor"), cmd ← no color;
        end
      end
    end
  end
  case rgb values do
    | (model, values) ← ("rgb", (r,g,b));
    | cmd ← output();
  end
  case without model do
    | if with xcolor then
      | (model, values) ← get model and values(value);
      switch model do
        case gray, rgb, cmyk do
          | cmd ← output();
        end
        case Gray do
          | (model, values) ← convert to gray;
          | cmd ← output();
        end
        else
          | (model, values) ← convert to rgb;
          | cmd ← output();
        end
      end
    else
      | error(package, option, "Missing xcolor"), cmd ← no color;
    end
  end

```

\HyColor@XZeroOneThreeFour

```
210 \def\HyColor@XZeroOneThreeFour#1#2#3#4{%
211   \HyColor@IfModel{#1}{%
212     \ifx\HyColor@model\HyColor@model@empty
213       \let#2\@empty
214     \else\ifx\HyColor@model\HyColor@model@gray
215       \expandafter\HyColor@NormalizeNum
216       \expandafter{\HyColor@values}#2%
217     \else\ifx\HyColor@model\HyColor@model@rgb
218       \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
219     \else\ifx\HyColor@model\HyColor@model@cmyk
220       \expandafter\HyColor@NormalizeCommaCMYK\HyColor@values\@nil#2%
221     \else\ifx\HyColor@model\HyColor@model@Gray
222       \HyColor@IfXcolor{%
223         \convertcolorspec\HyColor@model\HyColor@values
224           \HyColor@model@gray#2%
225         \expandafter\HyColor@NormalizeNum\expandafter{#2}#2%
226         \let\HyColor@model\HyColor@model@gray
227       }{%
228         \let#2\relax
229         \HyColor@ErrorModelNoXcolor{#3}{#4}%
230       }%
231     \else
232       \HyColor@IfXcolor{%
233         \convertcolorspec\HyColor@model\HyColor@values
234           \HyColor@model@rgb#2%
235         \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
236         \let\HyColor@model\HyColor@model@rgb
237       }{%
238         \let#2\relax
239         \HyColor@ErrorModelNoXcolor{#3}{#4}%
240       }%
241       \fi\fi\fi\fi\fi
242     }{%
243       \let#2\HyColor@values
244       \ifx#2\@empty
245         \let#2\relax
246       \else
247         \expandafter\HyColor@IfRGB\expandafter{\HyColor@values}{%
248           \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
249         }{%
250           \HyColor@IfXcolor{%
251             \expandafter\extractcolorspec\expandafter{\HyColor@values}#2%
252             \edef\HyColor@model{\expandafter\@firstoftwo#2}%
253             \edef\HyColor@values{\expandafter\@secondoftwo#2}%
254             \ifx\HyColor@model\HyColor@model@gray
255               \expandafter\HyColor@NormalizeNum\expandafter
256               {\HyColor@values}#2%
257             \else\ifx\HyColor@model\HyColor@model@rgb
258               \expandafter\HyColor@NormalizeCommaRGB
259               \HyColor@values\@nil#2%
260             \else\ifx\HyColor@model\HyColor@model@cmyk
261               \expandafter\HyColor@NormalizeCommaCMYK
262               \HyColor@values\@nil#2%
263             \else\ifx\HyColor@model\HyColor@model@Gray
264               \convertcolorspec\HyColor@model\HyColor@values
265                 \HyColor@model@gray#2%
266               \expandafter\HyColor@NormalizeNum\expandafter
267               {\HyColor@values}#2%
268               \let\HyColor@model\HyColor@model@gray
269             \else
270               \convertcolorspec\HyColor@model\HyColor@values
```

```

271      \HyColor@model@rgb#2%
272      \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
273      \let\HyColor@model\HyColor@model@rgb
274      \fi\fi\fi\fi
275      }%
276      \let#2\relax
277      \HyColor@ErrorSpecNoXcolor{#3}{#4}%
278      }%
279      }%
280      \fi
281      }%
282 }

```

2.5.3 Field options

```
\HyColor@FieldBColor
283 \let\HyColor@FieldBColor\HyColor@XZeroOneThreeFour
```

```
\HyColor@FieldColor
284 \def\HyColor@FieldColor#1#2#3#4{%
285   \let\HyColor@model\@empty
286   \HyColor@XZeroOneThreeFour{#1}{#2}{#3}{#4}%
287   \ifx#2\relax
288     \let#2\@empty
289   \else
290     \ifx#2\@empty
291       \else
292         \ifx\HyColor@model\HyColor@model@gray
293           \edef#2{\#2 g}%
294         \else\ifx\HyColor@model\HyColor@model@rgb
295           \edef#2{\#2 rg}%
296         \else\ifx\HyColor@model\HyColor@model@cmyk
297           \edef#2{\#2 k}%
298         \else
299           \PackageError{#3}{Internal error: unsupported color model}\@ehc
300           \fi\fi\fi
301       \fi
302     \fi
303 }
```

2.5.4 Detection for naked RGB values

```
\HyColor@IfRGB
304 \newif\ifHyColor@result
305 \begingroup\expandafter\expandafter\expandafter\endgroup
306 \expandafter\ifx\csname pdfmatch\endcsname\relax
307   \expandafter\@firstoftwo
308 \else
309   \expandafter\@secondoftwo
310 \fi
311 }%
312 \begingroup
313   \def\x#1{\endgroup
314   \def\HyColor@IfRGB##1{%
315     \HyColor@@IfRGB##1#1#1\@nil
316   }%
317   }%
318 \x{ }%
319 \edef\HyColor@TwoSpaces{\space\space}%
320 \def\HyColor@@IfRGB#1 #2 #3 #4\@nil{%
321   \HyColor@resulttrue
322   \def\HyColor@temp{#4}%

```

```

323   \ifx\HyColor@temp\HyColor@TwoSpaces
324     \HyColor@CheckNum{#1}%
325     \ifHyColor@result
326       \HyColor@CheckNum{#2}%
327       \ifHyColor@result
328         \HyColor@CheckNum{#3}%
329       \fi
330     \fi
331   \else
332     \HyColor@resultfalse
333   \fi
334   \ifHyColor@result
335     \let\HyColor@model\HyColor@model@rgb
336     \edef\HyColor@values{#1,#2,#3}%
337     \expandafter\@firstoftwo
338   \else
339     \expandafter\@secondoftwo
340   \fi
341 }%
342 \def\HyColor@zero{0}%
343 \def\HyColor@one{1}%
344 \def\HyColor@dot{.}%
345 \def\HyColor@CheckNum#1{%
346   \def\HyColor@temp{#1}%
347   \ifx\HyColor@temp\@empty
348     \HyColor@resultfalse
349   \else
350     \edef\HyColor@temp{\@car#1\@nil}%
351     \ifx\HyColor@temp\HyColor@zero
352     \else
353       \ifx\HyColor@temp\HyColor@one
354     \else
355       \ifx\HyColor@temp\HyColor@dot
356     \else
357       \HyColor@resultfalse
358     \fi
359   \fi
360   \fi
361 }%
362 }%
363 }{%
364 \def\HyColor@MatchNum{%
365   (0*1\string\.{0*1|0+\string\.{?0-9}*|\string\.{[0-9]+})%
366 }%
367 \def\HyColor@IfRGB#1{%
368   \ifnum\pdfmatch{^}\HyColor@MatchNum\space\HyColor@MatchNum
369     \space\HyColor@MatchNum$}{#1}>\z@
370   \let\HyColor@model\HyColor@model@rgb
371   \edef\HyColor@values{%
372     \expandafter\strip@prefix\pdflastmatch1,%
373     \expandafter\strip@prefix\pdflastmatch2,%
374     \expandafter\strip@prefix\pdflastmatch3%
375   }%
376   \HyColor@resulttrue
377   \expandafter\@firstoftwo
378   \else
379     \HyColor@resultfalse
380     \expandafter\@secondoftwo
381   \fi
382 }%
383 }

```

2.5.5 Options *bordercolor

Procedure HyperrefBorderColor(value, cmd, package, option)

Param: *value* (value of the option)
Param: *cmd* (macro for result)
Param: *package, option* (package and option for error message)

```

switch value do
  case empty do
    | cmd ← no color;
  end
  case with model do
    | if with xcolor then
      | | (model, values) ← convert to rgb;
      | | cmd ← output values;
    else
      | | switch model do
        | | | case rgb, gray do
        | | | | cmd ← output values;
        | | | end
        | | | else
        | | | | error(package, option, "Missing xcolor");
        | | | | cmd ← no color;
        | | | end
      | | end
    end
  end
  case rgb values do
    | cmd ← output values;
  end
  case without model do
    | if with xcolor then
      | | (model, values) ← convert to rgb;
      | | cmd ← output values;
    else
      | | error(package, option, "Missing xcolor"); cmd ← no color;
    end
  end
end
```

\HyColor@HyperrefBorderColor

```

384 \def\HyColor@HyperrefBorderColor#1#2#3#4{%
385   \HyColor@IfModel{#1}{%
386     \HyColor@IfXcolor{%
387       \convertcolorspec\HyColor@model\HyColor@values
388         \HyColor@model@rgb#2%
389       \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
390     }%
391     \ifx\HyColor@model\HyColor@model@rgb
392       \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
393     \else
394       \ifx\HyColor@model\HyColor@model@gray
395         \expandafter\HyColor@NormalizeNum
396           \expandafter{\HyColor@values}#2%
397         \edef#2{#2 #2 #2}%
398       \else
399         \let#2\relax
400         \HyColor@ModelErrorNoXcolor{#3}{#4}%

```

```

401      \fi
402      \fi
403      }%
404  }{%
405      \let#2\HyColor@values
406      \ifx#2\@empty
407          \let#2\relax
408      \else
409          \expandafter\HyColor@IfRGB\expandafter{\HyColor@values}{%
410              \expandafter\HyColor@NormalizeCommaRGB\HyColor@values\@nil#2%
411          }{%
412              \HyColor@IfXcolor{%
413                  \extractcolorspec{#1}#2%
414                  \expandafter\convertcolorspec#2\HyColor@model@rgb#2%
415                  \expandafter\HyColor@NormalizeCommaRGB#2\@nil#2%
416              }{%
417                  \let#2\relax
418                  \HyColor@ErrorSpecNoXcolor{#3}{#4}%
419              }%
420          }%
421      \fi
422  }%
423 }

```

2.6 Package **attachfile2**

Before PDF-1.7 only RGB values are permitted in annotations. Since PDF-1.7 the color entry in annotations understands several color models, depending on the size of the color array:

- Zero entries: means transparent, not useful for file attachments. AR7/Linux and AR8/Linux show black instead.
- One entry: color model ‘gray’.
- Three entries: color model ‘rgb’.
- Four entries: color model ‘cmyk’.

An empty color specification is interpreted as “no color”.

```
\HyColor@DetectPdfVersion
424 \def\HyColor@DetectPdfVersion{%
425   \begingroup\expandafter\expandafter\expandafter\endgroup
426   \expandafter\ifx\csname Hy@pdfversion\endcsname\relax
427     \global\chardef\HyColor@PdfVersion=0 %
428   \else
429     \global\chardef\HyColor@PdfVersion=\Hy@pdfversion\relax
430   \fi
431   \global\let\HyColor@DetectPdfVersion\relax
432 }
```

```
\HyColor@SpaceToComma
433 \def\HyColor@SpaceToComma#1 #2\@nil{%
434   #1%
435   \ifx\relax#2\relax
436       \expandafter\@gobble
437   \else
438     ,%
439     \expandafter\@firstofone
440   \fi
441   t%
442   \HyColor@SpaceToComma#2\@nil
```

```

443 }%
444 }%}

\HyColor@AttachfileColor
445 \def\HyColor@AttachfileColor#1#2#3#4#5#6{%
446   \def#2{\empty}
447   \ifx#2\empty
448     \let#3\empty
449     \let#4\empty
450   \else
451     \HyColor@resultfalse
452     \HyColor@XZeroOneThreeFour{#1}{#3}{#5}{#6}%
453     \ifHyColor@result
454       \edef#2{%
455         [rgb]{\expandafter\HyColor@SpaceToComma#3 \@nil}%
456       }%
457     \fi
458   \ifx\HyColor@model\HyColor@model@rgb
459     \edef#4{/C[#3]}% hash-ok
460     \edef#3##1{%
461       #3 %
462       \noexpand\csname atfi@SETRGBCOLOR##1\noexpand\endcsname
463     }%
464   \else
465     \ifx\HyColor@model\HyColor@model@gray
466       \HyColor@DetectPdfVersion
467       \ifnum\HyColor@PdfVersion<7 %
468         \edef#4{/C[#3 #3 #3]}% hash-ok
469       \else
470         \edef#4{/C[#3]}% hash-ok
471       \fi
472       \edef#3##1{%
473         #3 %
474         \noexpand\csname atfi@SETGRAYCOLOR##1\noexpand\endcsname
475       }%
476     \else
477       \ifx\HyColor@model\HyColor@model@cmyk
478         \HyColor@DetectPdfVersion
479         \ifnum\HyColor@PdfVersion<7 %
480           \HyColor@IfModel{#1}{%
481             \HyColor@IfXcolor{%
482               \convertcolorspec\HyColor@model\HyColor@values
483               \HyColor@model@rgb#4%
484               \expandafter\HyColor@NormalizeCommaRGB#4\@nil#4%
485               \edef#4{/C[#4]}% hash-ok
486             }%
487             \let#4\empty
488             \HyColor@ModelErrorNoXcolor{#5}{#6}%
489           }%
490         }%
491         \HyColor@IfXcolor{%
492           \extractcolorspec{#1}#4%
493           \expandafter\convertcolorspec#4%
494             \HyColor@model@rgb#4%
495             \expandafter\HyColor@NormalizeCommaRGB#4\@nil#4%
496             \edef#4{/C[#4]}% hash-ok
497           }%
498           \let#4\empty
499           \HyColor@ModelErrorSpecNoXcolor{#5}{#6}%
500         }%
501       }%
502     \else
503       \edef#4{/C[#3]}% hash-ok

```

```

504      \fi
505      \edef#3##1{%
506          #3 %
507          \noexpand\csname atfi@SETCMYKCOLOR##1\noexpand\endcsname
508      }%
509  \else
510      \ifx\HyColor@model\HyColor@model@empty
511          \PackageError{#5}{%
512              Color model 'empty' is not permitted for option '#6'
513          }@\ehc
514          \let#2\@empty
515          \let#3\@gobble
516          \let#4\@empty
517      \else
518          \ifx\HyColor@model\relax % (missing xcolor)
519              \let#3\@gobble
520              \let#4\@empty
521          \else
522              \PackageError{#5}{%
523                  Internal error: unsupported color model%
524              }@\ehc
525          \fi
526      \fi
527      \fi
528      \fi
529      \fi
530  \fi
531 }

532 </package>

```

2.7 Patch for package `xcolor`

Because the test files triggered a bug in package `xcolor` of version 2007/01/21 v2.11. I contacted the author of `xcolor` Uwe Kern. He responded with a test version 2007/03/27 v2.12a00 that fixes the problem. However, apparently he did not find the time for an official release yet. Thus I have reluctantly written the following patch package using the fixes of v2.12a00.

The patch is immediately applied if package `xcolor` is already loaded. Otherwise the patch is delayed using `\AfterPackage` if package `scrlfile` is loaded. As last resort `\AtBeginDocument` is used.

```

533 {*xcolor}
534 \NeedsTeXFormat{LaTeX2e}
535 \ProvidesPackage{xcolor-patch}[2016/05/16 xcolor patch]
536 \RequirePackage{hopatch}[2016/05/16]
537 \hopatch@AfterPackage{xcolor}{%

```

```

\XC@ifxcase
538 \long\def\reserved@a#1#2#3{%
539     \long\def\@tmp##1##2{%
540         \ifx##1##1%
541             \toks@{##2}%
542             \expandafter\remove@to@nnil
543         \else
544             \expandafter\@tmp
545         \fi
546     }%
547     \@@tmp##1##3\@nnil\the\toks@
548 }%
549 \ifx\XC@ifxcase\reserved@a
550     \long\def\XC@ifxcase#1#2#3{%

```

```

551      \long\def\XC@if@##1##2{%
552          \ifx#1##1%
553              \toks@\{\##2\}%
554              \expandafter\remove@to@nnil
555          \else
556              \expandafter\XC@if@
557          \fi
558      }%
559      \XC@if@##2{#1}{#3}\@nnil
560      \the\toks@
561  }%
562 \fi

\XC@ifcase
563 \long\def\reserved@a#1#2#3{%
564     \long\def\@@tmp##1##2{%
565         \expandtwoargs\in@{,#1}{,##1,}%
566         \ifin@%
567             \toks@\{\##2\}%
568             \expandafter\remove@to@nnil
569         \else
570             \expandafter\@@tmp
571         \fi
572     }%
573     \@@tmp##2{#1}{#3}\@nnil
574     \the\toks@
575 }%
576 \ifx\XC@ifcase\reserved@a
577     \long\def\XC@ifcase#1#2#3{%
578         \long\def\XC@if@##1##2{%
579             \expandtwoargs\in@{,#1}{,##1,}%
580             \ifin@%
581                 \toks@\{\##2\}%
582                 \expandafter\remove@to@nnil
583             \else
584                 \expandafter\XC@if@
585             \fi
586         }%
587         \XC@if@##2{#1}{#3}\@nnil
588         \the\toks@
589     }%
590 \fi

\XC@cnv@gray
591 \def\reserved@a#1{%
592     \XC@ifxcase\tmf{%
593         \XC@mod@rgb{%
594             \XC@calcN{#1}\@@tmp
595             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
596         }%
597         \XC@mod@cmy{%
598             \XC@calcC{#1}\@@tmp
599             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
600         }%
601         \XC@mod@cmyk{%
602             \XC@calcC{#1}\@@tmp
603             \edef\@@tmp{0,0,0,\@@tmp}%
604         }%
605         \XC@mod@RGB{%
606             \edef\@@scl`rangeRGB}%
607             \XC@calcM{#1}\@@tmp
608             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
609         }%

```

```

610      \XC@mod@HTML{%
611          \edef\@@scl{\@cclv}%
612          \XC@calcM{\#1}\@@tmp
613          \XC@calcH\@@tmp\@@tmp
614          \edef\@@tmp{\@@tmp\@@tmp\@@tmp}%
615      }%
616      \XC@mod@HSB{%
617          \edef\@@scl{\rangeHSB}%
618          \XC@calcM{\#1}\@@tmp
619          \edef\@@tmp{0,0,\@@tmp}%
620      }%
621      \XC@mod@Gray{%
622          \edef\@@scl{\rangeGray}%
623          \XC@calcM{\#1}\@@tmp
624      }%
625  }%
626  {%
627      \XC@calcN{\#1}\@@tmp
628      \edef\@@tmp{0,0,\@@tmp}%
629  }%
630 }%
631 \ifx\XC@cnv@gray\reserved@a
632 \def\XC@cnv@gray#1,{%
633     \XC@ifxcase\tm{%
634         \XC@mod@rgb{%
635             \XC@calcN{\#1}\@@tmp
636             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
637         }%
638         \XC@mod@gray{}%
639         \XC@mod@cmy{%
640             \XC@calcC{\#1}\@@tmp
641             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
642         }%
643         \XC@mod@cmyk{%
644             \XC@calcC{\#1}\@@tmp
645             \edef\@@tmp{0,0,0,\@@tmp}%
646         }%
647         \XC@mod@RGB{%
648             \edef\@@scl{\rangeRGB}%
649             \XC@calcM{\#1}\@@tmp
650             \edef\@@tmp{\@@tmp,\@@tmp,\@@tmp}%
651         }%
652         \XC@mod@HTML{%
653             \edef\@@scl{\@cclv}%
654             \XC@calcM{\#1}\@@tmp
655             \XC@calcH\@@tmp\@@tmp
656             \edef\@@tmp{\@@tmp\@@tmp\@@tmp}%
657         }%
658         \XC@mod@HSB{%
659             \edef\@@scl{\rangeHSB}%
660             \XC@calcM{\#1}\@@tmp
661             \edef\@@tmp{0,0,\@@tmp}%
662         }%
663         \XC@mod@Gray{%
664             \edef\@@scl{\rangeGray}%
665             \XC@calcM{\#1}\@@tmp
666         }%
667     }%
668     {%
669         \XC@calcN{\#1}\@@tmp
670         \edef\@@tmp{0,0,\@@tmp}%
671     }%

```

```

672    }%
673 \fi

```

2.7.1 Fix fragile \framebx

\fbox becomes fragile, because the internal \framebx is redefined by package xcolor. The redefinition is no longer robust. Test file:

```

\documentclass{article}
\usepackage{xcolor}
\makeatletter
\protected@edef\x{\fbox{abc}}
\@@end

674 \@ifundefined{XC@framebx }{%
675   \expandafter\let\csname XC@framebx \endcsname\XC@framebx
676   \edef\XC@framebx{%
677     \noexpand\protect
678     \expandafter\noexpand\csname XC@framebx \endcsname
679   }%
680   \expandafter\ifx\csname XC@framebx \endcsname\@framebx
681   \let\@framebx\XC@framebx
682   \fi
683 }{}%
684 }

685 </xcolor>

```

3 Test

```

686 <*test1>
687 \ProvidesFile{hycolor-test1.tex}[2016/05/16 test file 1]
688 </test1>

689 <*test2>
690 \ProvidesFile{hycolor-test2.tex}[2016/05/16 test file 2]
691 \let\pdfmatch\relax
692 </test2>

693 <test3>\ProvidesFile{hycolor-test3.tex}[2016/05/16 test file 3]
694 <*test>

695 \documentclass{article}
696
697 \usepackage{qstest}
698 \IncludeTests{*}
699 \LogTests{log}{*}{*}
700
701 \makeatletter
702
703 \newcommand*\TestPackageName{test-package}
704 \newcommand*\TestOptionName{test-option}
705
706 \newcommand\Message{}
707 \def\Message#1{\immediate\write16}
708
709 \newcommand*\ExpectError[2]{%
710   \begingroup
711   \global\let\saved@errhelp\errhelp
712   \global\let\saved@errmessage\errmessage
713   \let\errhelp\@gobble
714   \def\errmessage##1{%
715     \xdef\@ExpectErrorMessage{##1}%
716   }%

```

```

717  \PackageError\TestPackageName{\#1}\@ehc
718  \def\errhelp##1{%
719    \global\let\errhelp\saved@errhelp
720  }%
721  \global\let\@ResultErrorMessage\empty
722  \def\errmessage##1{%
723    \xdef\@ResultErrorMessage{\#1}%
724    \global\let\errmessage\saved@errmessage
725    \% \Message{[ \#1]}%
726    \% \Message{} (ignored error)}%
727    \% \Message{}%
728  }%
729  #2%
730 \endgroup
731 \Expect*{\@ResultErrorMessage}*{\@ExpectErrorMessage}%
732 }
733 \usepackage{scrlfile}
734 \usepackage{hycolor}[2016/05/16]
735 
```

$$\langle *test1 \rangle$$

$$\begin{aligned} 737 \begin{qstest} \{ \text{NumNormalize} \} \{ \text{num, normalize} \} \\ 738 \def \text{test} \#1 \#2 { \% \\ 739 \quad \text{HyColor} @ \text{NormalizeNum} \{ \#1 \} \text{cmd} \\ 740 \quad \text{Expect*} \{ \text{cmd} \} \{ \#2 \} \% \\ 741 \} \% \\ 742 \text{test} \{ 0 \} \{ 0 \} \% \\ 743 \text{test} \{ 000 \} \{ 0 \} \% \\ 744 \text{test} \{ -1 \} \{ 0 \} \% \\ 745 \text{test} \{ 0 \} \{ 0 \} \% \\ 746 \text{test} \{ 1.1 \} \{ 1 \} \% \\ 747 \text{test} \{ 100 \} \{ 1 \} \% \\ 748 \text{test} \{ 00100 \} \{ 1 \} \% \\ 749 \text{test} \{ 99.99 \} \{ 1 \} \% \\ 750 \text{test} \{ 0.0 \} \{ 0 \} \% \\ 751 \text{test} \{ 00.00 \} \{ 0 \} \% \\ 752 \text{test} \{ 0. \} \{ 0 \} \% \\ 753 \text{test} \{ .0 \} \{ 0 \} \% \\ 754 \text{test} \{ 0.1 \} \{ .1 \} \% \\ 755 \text{test} \{ 0.10 \} \{ .1 \} \% \\ 756 \text{test} \{ 0.1000 \} \{ .1 \} \% \\ 757 \text{test} \{ .1000 \} \{ .1 \} \% \\ 758 \text{test} \{ 0.01 \} \{ .01 \} \% \\ 759 \text{test} \{ 0.01010 \} \{ .0101 \} \% \\ 760 \text{test} \{ .0000000001 \} \{ .0000000001 \} \% \\ 761 \text{test} \{ .9999999999 \} \{ .9999999999 \} \% \\ 762 \end{qstest} \\ 763 \begin{qstest} \{ \text{BookmarkColor without xcolor} \} \{ \text{bookmark, noxcolor} \} \\ 764 \def \text{test} \#1 \#2 { \% \\ 765 \quad \text{HyColor} @ \text{BookmarkColor} \{ \#1 \} \text{cmd} \text{TestPackageName} \text{TestOptionName} \\ 766 \quad \text{Expect*} \{ \text{cmd} \} \{ \#2 \} \% \\ 767 \} \% \\ 768 \text{test} \{ [rgb] \{ 1,0,0 \} \} \{ 1 \ 0 \ 0 \} \% \\ 769 \text{test} \{ [gray] \{ 0.10 \} \} \{ .1 \ .1 \ .1 \} \% \\ 770 \text{test} \{ \} \{ \} \% \\ 771 \text{test} \{ [rgb] \{ 1 , 1 , 0 \} \} \{ 1 \ 1 \ 0 \} \% \\ 772 \def \text{errortest} \#1 \#2 { \% \\ 773 \quad \text{ExpectError} \% \\ 774 \quad \text{Color model '}\#1\text{' is not supported}\MessageBreak \\ 775 \quad \text{without package '}\text{xcolor}\text{' in}\MessageBreak \\ 776 \quad '\text{TestOptionName}=[\#1]\{ \#2 \}' \% \text{ hash-ok} \\ 777 \} \% \\ 778 \end{qstest} \end{aligned}$$

```

779      \test{[#1]{#2}}{}% hash-ok
780  }%
781 }%
782 \errortest[cmyk]{1,0,0,0}%
783 \errortest[empty]{}%
784 \def\errortest#1{%
785   \ExpectError{%
786     This color specification is not supported\MessageBreak
787     without package `xcolor' in\MessageBreak
788     `TestOptionName=#1'%
789   }{%
790     \test{#1}{}%
791   }%
792 }%
793 \end{qstest}
794 
```

- 795 <*test1.j test2>
- 796 \begin{qstest}{X0134 without xcolor}{X0134, noxcolor}
- 797 \def\test#1#2{%
- 798 \HyColor@XZeroOneThreeFour{#1}\cmd\TestPackageName\TestOptionName
- 799 \Expect*{\cmd}{#2}%
- 800 }%
- 801 \test{[empty]}{}{}%
- 802 \test{[rgb]{1,0,0}}{1 0 0}%
- 803 \test{[gray]{0.10}}{.1}%
- 804 \test{[cmyk]{0,1,0,0}}{0 1 0 0}%
- 805 \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
- 806 \def\errortest[#1]#2{%
- 807 \ExpectError{%
- 808 Color model '#1' is not supported\MessageBreak
- 809 without package `xcolor' in\MessageBreak
- 810 `test-option=[#1]{#2}'% hash-ok
- 811 }{%
- 812 \HyColor@XZeroOneThreeFour{[{}#1]}{#2}\cmd
- 813 \TestPackageName\TestOptionName
- 814 \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
- 815 }%
- 816 }%
- 817 \errortest[Gray]{10}%
- 818 \errortest[cmyl]{1,0,0}%
- 819 \def\errortest#1{%
- 820 \ExpectError{%
- 821 This color specification is not supported\MessageBreak
- 822 without package `xcolor' in\MessageBreak
- 823 `test-option=#1'%
- 824 }{%
- 825 \HyColor@XZeroOneThreeFour{#1}\cmd\TestPackageName\TestOption-
Name
- 826 \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
- 827 }%
- 828 }%
- 829 \errortest{yellow}%
- 830 \end{qstest}
- 831
- 832 \begin{qstest}{HyperrefBorderColor without xcolor}%
- 833 {hyperef bordercolor, noxcolor}%
- 834 \def\test#1#2{%
- 835 \HyColor@HyperrefBorderColor{#1}\cmd\TestPackageName\TestOptionName
- 836 \Expect*{\cmd}{#2}%
- 837 }%
- 838 \test{[rgb]{1,0,0}}{1 0 0}%
- 839 \test{[gray]{0.10}}{.1 .1 .1}%

```

840 \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
841 \def\errortest[#1]#2{%
842   \ExpectError{%
843     Color model '#1' is not supported\MessageBreak
844     without package 'xcolor' in\MessageBreak
845     'test-option=[#1]{#2}'% hash-ok
846   }{%
847     \HyColor@HyperrefBorderColor{{#1}{#2}}\cmd
848     \TestPackageName\TestOptionName
849     \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
850   }%
851 }%
852 \errortest[Gray]{10}%
853 \errortest[cmy]{1,0,0}%
854 \errortest[cmyk]{0,1,0,0}%
855 \def\errortest#1{%
856   \ExpectError{%
857     This color specification is not supported\MessageBreak
858     without package 'xcolor' in\MessageBreak
859     'test-option=#1'%
860   }{%
861     \HyColor@HyperrefBorderColor{#1}\cmd
862     \TestPackageName\TestOptionName
863     \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
864   }%
865 }%
866 \errortest{yellow}%
867 \end{qstest}
868 {/test1 j test2}

869 {*test1 j test2}
870 \usepackage{xcolor}
871 \definecolor[named]{MyGreen}{rgb}{0,0.7,0}
872 \definecolor{mygreen}{named}{MyGreen}
873 {/test1 j test2}

874 {*test1}
875 \begin{qstest}{BookmarkColor with xcolor}{bookmark, xcolor}
876 \def\test#1#2{%
877   \HyColor@BookmarkColor{#1}\cmd\PackageName\OptionName
878   \Expect*{\cmd}{#2}%
879 }%
880 \test{[rgb]{1,0,0}}{1 0 0}%
881 \test{[gray]{0.10}}{.1 .1 .1}%
882 \test{}{}%
883 \test{[rgb]{ 1 , 1 , 0 }}{1 1 0}%
884 \test{[cmyk]{1,0,0,0}}{0 1 1}%
885 \test{[red]{1 0 0}}%
886 \test{[cyan]{0 1 1}}%
887 \test{[red!40!blue]{.4 0 .6}}%
888 \test{[Gray]{10}}{.66667 .66667 .66667}%
889 \test{[RGB]{100,200,50}}{.39217 .78432 .19609}%
890 \test{[wave]{363}}{.00316 0 .00316}%
891 \test{[wave]{814}}{.00797 0 0}%
892 \test{[HSB]{100,200,50}}{.03473 .20833 .12152}%
893 \test{[HTML]{A800FF}}{.65881 0 1}%
894 \test{[cmy]{.3,.5,.2}}{.7 .5 .8}%
895 \test{[cmyk]{.3,.5,.2,.1}}{.6 .4 .7}%
896 \test{[hsb]{.3,.5,.2}}{.12 .2 .1}%
897 \test{[Hsb]{120,.5,.2}}{.1 .2 .1}%
898 \test{[tHsb]{120,.5,.2}}{.2 .2 .1}%
899 \test{[named]{MyGreen}}{0 .7 0}%
900 \test{[mygreen]}{0 .7 0}%
901 \end{qstest}

```

```

902
903 \begin{qstest}{HyperrefColor}{hyperref, color}
904 \def\test#1#2{%
905   \HyColor@HyperrefColor{#1}\cmd
906   \Expect*\{\cmd\}{#2}%
907 }%
908 \test{red}{red}%
909 \test{[rgb]{1,0,0}}{[[rgb]{1,0,0}}%
910 \HyColor@HyperrefColor{}{\cmd
911 \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
912 \end{qstest}
913 
```

```

914 {*test1 j test2}
915 \begin{qstest}{X0134 with xcolor}{hyperref, X0134, xcolor}
916 \def\test#1#2{%
917   \HyColor@XZeroOneThreeFour{#1}\cmd\PackageName\OptionName
918   \Expect*\{\cmd\}{#2}%
919 }%
920 \test{[empty]}{}%
921 \test{[gray]{0.1}}{.1}%
922 \test{[rgb]{1,0.5,0.0}}{1 .5 0}%
923 \test{[cmyk]{0,1,0,0.5}}{0 1 0 .5}%
924 \test{[Gray]{10}}{.666667}%
925 \test{red}{1 0 0}%
926 \test{1 0 0}{1 0 0}%
927 \test{001.0 .23 0}{1 .23 0}%
928 \test{[named]{MyGreen}}{0 .7 0}%
929 \test{mygreen}{0 .7 0}%
930 \HyColor@XZeroOneThreeFour{}{\cmd\PackageName\OptionName
931 \Expect{true}*{\ifx\cmd\relax true\else false\fi}%
932 \end{qstest}
933 
```

```

934 \begin{qstest}{FieldColor}{hyperref, field, FieldColor}
935 \def\test#1#2{%
936   \HyColor@FieldColor{#1}\cmd\PackageName\OptionName
937   \Expect*\{\cmd\}{#2}%
938 }%
939 \test{}{}%
940 \test{[gray]{0.7}}{.7 g}%
941 \test{[rgb]{1,0,0}}{1 0 0 rg}%
942 \test{[cmyk]{0,1,0,0}}{0 1 0 0 k}%
943 \test{[cmy]{.5,.4,.3}}{.5 .6 .7 rg}%
944 \end{qstest}
945 
```

3.1 Test for package **attachfile2**

```

946 {*test3}
947 \def\atfi@SETRGBCOLORtest{set-rgb}
948 \def\atfi@SETGRAYCOLORtest{set-gray}
949 \def\atfi@SETCMYKCOLORtest{set-cmyk}
950 \def\Test#1#2#3#4#5{%
951   \begingroup
952   \setbox0=\hbox{%
953     \begingroup
954       \chardef\HyColor@PdfVersion=6 %
955       \HyColor@AttachfileColor{#1}\spec\inlinemacro\annot
956         \TestPackageName\TestOptionName
957       \edef\inline{\inlinemacro{test}}%
958       \expandafter\Expect\expandafter{\spec}{#2}%
959       \expandafter\Expect\expandafter{\inline}{#3}%
960       \expandafter\Expect\expandafter{\annot}{#4}%
961     \endgroup
962   }
```

```

962      \begingroup
963          \chardef\HyColor@PdfVersion=7 %
964          \HyColor@AttachfileColor{\#1}\spec\inlinemacro\annot
965              \TestPackageName\TestOptionName
966          \edef\inline{\inlinemacro{test}}%
967          \expandafter\Expect\expandafter{\spec}{\#2}%
968          \expandafter\Expect\expandafter{\inline}{\#3}%
969          \expandafter\Expect\expandafter{\annot}{\#5}%
970      \endgroup
971  }%
972  \Expect*{\the\wd0}{0.0pt}%
973 \endgroup
974 }%
975 \newif\ifError
976 \def\TestError[#1]#2#3#4#5#6{%
977     \begingroup
978         \global\Errorfalse
979         \let\OrgPackageError\PackageError
980         \def\PackageError##1##2##3{%
981             \edef\TestTemp{##1}%
982             \ifx\TestTemp\TestPackageName
983                 \Expect*{\ifError too many errors\else ok\fi}{ok}%
984                 \Expect*{#6}{##2}%
985                 \global\Errortrue
986             \else
987                 \OrgPackageError{##1}{##2}{##3}%
988             \fi
989         }%
990         \setbox0=\hbox{%
991             \begingroup
992                 \chardef\HyColor@PdfVersion=#1 %
993                 \HyColor@AttachfileColor{\#2}\spec\inlinemacro\annot
994                     \TestPackageName\TestOptionName
995                 \edef\inline{\inlinemacro{test}}%
996                 \expandafter\Expect\expandafter{\spec}{\#3}%
997                 \expandafter\Expect\expandafter{\inline}{\#4}%
998                 \expandafter\Expect\expandafter{\annot}{\#5}%
999             \endgroup
1000             \ifx\#\#6\%
1001             \else
1002                 \Expect*{\ifError ok\else missing error\fi}{ok}%
1003             \fi
1004         }%
1005         \Expect*{\the\wd0}{0.0pt}%
1006     \endgroup
1007 }%
1008 \def\NoEmptyModel{%
1009     Color model 'empty' is not permitted for option '\TestOptionName'%
1010 }%
1011 \def\ModelNoXcolor#1#2{%
1012     Color model '#1' is not supported\MessageBreak
1013     without package 'xcolor' in\MessageBreak
1014     '\TestOptionName=[#1]{#2}'% hash-ok
1015 }%
1016 \def\SpecNoXColor#1{%
1017     This color specification is not supported\MessageBreak
1018     without package 'xcolor' in\MessageBreak
1019     'test-option=#1'%
1020 }%
1021 \begin{qstest}{AttachfileColor}{AttachfileColor}
1022     \Test{}{}{}{}{%
1023         \Test{0.1 0.2 0.3}{[rgb]{.1,.2,.3}}{.1 .2 .3 set-rgb}%

```

```

1024     {/C[.1 .2 .3]}{/C[.1 .2 .3]}%
1025 \Test{[gray]{0.4}}{[gray]{0.4}}{.4 set-gray}%
1026     {/C[.4 .4 .4]}{/C[.4]}%
1027 \Test{[rgb]{0.3,.2,.1}}{[rgb]{0.3,.2,.1}}{.3 .2 .1 set-rgb}%
1028     {/C[.3 .2 .1]}{/C[.3 .2 .1]}%
1029 \Test{0.0 1.0 1}{[rgb]{0,1,1}}{0 1 1 set-rgb}%
1030     {/C[0 1 1]}{/C[0 1 1]}%
1031 \Test{[gray]1}{[gray]1}{1 set-gray}{/C[1 1 1]}{/C[1]}%
1032 \TestError{6}{[empty]{}}{}{}{\NoEmptyModel}
1033 \TestError{7}{[empty]{}}{}{}{\NoEmptyModel}
1034 \TestError{6}{[cmyk]{.1,.2,.3,.4}}{[cmyk]{.1,.2,.3,.4}}%
1035     {.1 .2 .3 .4 set-cmyk}{}%
1036     {\ModelNoXcolor{cmyk}{.1,.2,.3,.4}}%
1037 \TestError{7}{[cmyk]{.1,.2,.3,.4}}{[cmyk]{.1,.2,.3,.4}}%
1038     {.1 .2 .3 .4 set-cmyk}{/C[.1 .2 .3 .4]}{}%
1039 \TestError{6}{red}{red}{}{}{\SpecNoXColor{red}}%
1040 \TestError{7}{red}{red}{}{}{\SpecNoXColor{red}}%
1041 \end{qstest}

1042 \usepackage{xcolor}
1043 \definecolor[named]{MyGreen}{rgb}{0,0.7,0}
1044 \definecolor{mygreen}{named}{MyGreen}
1045 \definecolor{graynine}{gray}{0.9}
1046 \definecolor{GraySix}{Gray}{9}

1047 \begin{qstest}{AttachfileColorX}{AttachfileColorX}
1048   \Test{}{}{}{}{}%
1049   \Test{0.1 0.2 0.3}{[rgb]{.1,.2,.3}}{.1 .2 .3 set-rgb}%
1050     {/C[.1 .2 .3]}{/C[.1 .2 .3]}%
1051   \Test{[gray]{0.4}}{[gray]{0.4}}{.4 set-gray}%
1052     {/C[.4 .4 .4]}{/C[.4]}%
1053   \Test{[rgb]{0.3,.2,.1}}{[rgb]{0.3,.2,.1}}{.3 .2 .1 set-rgb}%
1054     {/C[.3 .2 .1]}{/C[.3 .2 .1]}%
1055 \Test{0.0 1.0 1}{[rgb]{0,1,1}}{0 1 1 set-rgb}%
1056     {/C[0 1 1]}{/C[0 1 1]}%
1057 \Test{[gray]1}{[gray]1}{1 set-gray}{/C[1 1 1]}{/C[1]}%
1058 \Test{red}{red}{1 0 0 set-rgb}{/C[1 0 0]}{/C[1 0 0]}%
1059 \Test{black}{black}{0 set-gray}{/C[0 0 0]}{/C[0]}%
1060 \Test{cyan}{cyan}{1 0 0 0 set-cmyk}{/C[0 1 1]}{/C[1 0 0 0]}%
1061 \Test{[named]{black}}{[named]{black}}{0 0 0 set-rgb}%
1062     {/C[0 0 0]}{/C[0 0 0]}%
1063 \Test{[Gray]{9}}{[Gray]{9}}{.6 set-gray}{/C[.6 .6 .6]}{/C[.6]}%
1064 \Test{[HTML]{0080FF}}{[HTML]{0080FF}}{0 .50195 1 set-rgb}%
1065     {/C[0 .50195 1]}{/C[0 .50195 1]}%
1066 \Test{graynine}{graynine}{.9 set-gray}{/C[.9 .9 .9]}{/C[.9]}%
1067 \Test{GraySix}{GraySix}{.6 set-gray}{/C[.6 .6 .6]}{/C[.6]}%
1068 \Test{[wave]{500}}{[wave]{500}}{0 1 .49846 set-rgb}%
1069     {/C[0 1 .49846]}{/C[0 1 .49846]}%
1070 \TestError{6}{[empty]{}}{}{}{\NoEmptyModel}
1071 \TestError{7}{[empty]{}}{}{}{\NoEmptyModel}
1072 \end{qstest}

1073 </test3>
1074 <*test>
1075 \begin{document}
1076 \end{document}
1077 </test>

3.2 Test for package xcolor

1078 <*test-xcolor>
1079 \NeedsTeXFormat{LaTeX2e}
1080 \nofiles
1081 \documentclass{minimal}
1082 <*xcol1>

```

```

1083 \usepackage{xcolor}
1084 \usepackage{xcolor-patch}[2016/05/16]
1085 </xcol1>
1086 <*xcol2>
1087 \usepackage{scrlfile}
1088 \usepackage{xcolor-patch}[2016/05/16]
1089 \usepackage{xcolor}
1090 </xcol2>
1091 <*xcol3>
1092 \usepackage{xcolor-patch}[2016/05/16]
1093 \usepackage{xcolor}
1094 \begin{document}
1095 </xcol3>
1096 \makeatletter
1097 \newcommand*\ColModList[1]{%
1098   #1,
1099   cmy,%
1100   cmyk,%
1101   hsb,%
1102   Hsb,%
1103   tHsb,%
1104   gray,%
1105   RGB,%
1106   HTML,%
1107   HSB,%
1108   Gray,%
1109   wave,
1110 }
1111 \newcommand*\StartModel[1]{#1}
1112 \newcommand*\StartValues[1]{#1}
1113 \for\x:=\ColModList\do{%
1114   \ifx\x\empty
1115     \else
1116       \convertcolorspec\StartModel\StartValues\x\y
1117       \typeout{* [\StartModel]\StartValues} ==> [\x]\y}%
1118 \for\xx:=\ColModList\do{%
1119   \ifx\xx\empty
1120     \else
1121       \convertcolorspec\x\y\xx\yy
1122       \typeout{* \x\y ==> \xx\yy}%
1123     \fi
1124   }%
1125 \fi
1126 }
1127 <xcol3>\end{document}
1128 <xcol1 j xcol2>\@end
1129 </test-xcolor>

```

3.2.1 Test for \framebox/\fbox

```

1130 <*test-xcolor-fbox>
1131 \NeedsTeXFormat{LaTeX2e}
1132 \documentclass{article}
1133 \usepackage{xcolor}
1134 \usepackage{xcolor-patch}[2016/05/16]
1135 \makeatletter
1136 \protected@edef\x{\fbox{abc}}
1137 \let\@tempa\@undefined
1138 \protected@edef\x{\fbox{abc}}
1139 \makeatother
1140 \begin{document}
1141 \MakeUppercase{\fbox{abc}}
1142 \end{document}
1143 </test-xcolor-fbox>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/hycolor.dtx](http://ctan.org/macros/latex/contrib/oberdiek/hycolor.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/hycolor.pdf](http://ctan.org/macros/latex/contrib/oberdiek/hycolor.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/install/macros/latex/contrib/oberdiek.tds.zip)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:tds/tds.pdf](http://ctan.org/tds/tds.pdf)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDs:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain TeX:

```
tex hycolor.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

| | |
|--|---|
| <code>hycolor.sty</code> | → <code>tex/latex/oberdiek/hycolor.sty</code> |
| <code>xcolor-patch.sty</code> | → <code>tex/latex/oberdiek/xcolor-patch.sty</code> |
| <code>hycolor.pdf</code> | → <code>doc/latex/oberdiek/hycolor.pdf</code> |
| <code>test/hycolor-test1.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test1.tex</code> |
| <code>test/hycolor-test2.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test2.tex</code> |
| <code>test/hycolor-test3.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test3.tex</code> |
| <code>test/hycolor-test-xcol1.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test-xcol1.tex</code> |
| <code>test/hycolor-test-xcol2.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test-xcol2.tex</code> |
| <code>test/hycolor-test-xcol3.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test-xcol3.tex</code> |
| <code>test/hycolor-test-xcol4.tex</code> | → <code>doc/latex/oberdiek/test/hycolor-test-xcol4.tex</code> |
| <code>hycolor.dtx</code> | → <code>source/latex/oberdiek/hycolor.dtx</code> |

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

¹<http://ctan.org/pkg/hycolor>

4.4 Refresh file name databases

If your **TEX** distribution (teTEX, mikTEX, ...) relies on file name databases, you must refresh these. For example, teTEX users run **texhash** or **mktexlsr**.

4.5 Some details for the interested

Unpacking with LATEX. The .dtx chooses its action depending on the format:

plain TEX: Run docstrip and extract the files.

LATEX: Generate the documentation.

If you insist on using LATEX for docstrip (really, **docstrip** does not need LATEX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hycolor.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file **ltxdoc.cfg**. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfLATEX:

```
pdflatex hycolor.dtx
makeindex -s gind.ist hycolor.idx
pdflatex hycolor.dtx
makeindex -s gind.ist hycolor.idx
pdflatex hycolor.dtx
```

5 Catalogue

The following XML file can be used as source for the **TEX Catalogue**. The elements **caption** and **description** are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is **hycolor.xml**.

```
1144 <catalogue>
1145 <?xml version='1.0' encoding='us-ascii'?>
1146 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
1147 <entry datestamp='$Date$' modifier='$Author$' id='hycolor'>
1148   <name>hycolor</name>
1149   <caption>Implements colour for packages hyperref and bookmark.</caption>
1150   <authorref id='auth:oberdiek' />
1151   <copyright owner='Heiko Oberdiek' year='2007-2011' />
1152   <license type='lppl1.3' />
1153   <version number='1.8' />
1154   <description>
1155     This package provides the code for the color option
1156     that is used by packages <xref refid='hyperref'>hyperref</xref>
1157     and <xref refid='bookmark'>bookmark</xref>.
1158     It is not intended as package for the user.
1159     <p/>
1160     The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
1161   </description>
1162   <documentation details='Package documentation'
1163     href='ctan:/macros/latex/contrib/oberdiek/hycolor.pdf' />
1164   <ctan file='true' path='/macros/latex/contrib/oberdiek/hycolor.dtx' />
1165   <miktex location='oberdiek' />
```

```

1166 <texlive location='oberdiek' />
1167 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
1168 </entry>
1169 </catalogue>

```

6 History

[2007/04/09 v1.0]

- First version.

[2007/04/11 v1.1]

- Line ends sanitized.

[2008/07/29 v1.2]

- Support for package `attachfile2` added.

[2008/08/01 v1.3]

- Patch package `xcolor-patch` added that fixes bugs in package `xcolor` to get the test files running.

[2008/09/08 v1.4]

- Fix added to package `xcolor-patch`: Fragile `\@frameb@x` (used in `\fbox`) is made robust.

[2009/10/02 v1.5]

- Doku fixes (Herbert Voss).

[2009/12/12 v1.6]

- Short info shortened.

[2011/01/30 v1.7]

- Package `xcolor-patch` uses package `hopatch`.

[2016/05/16 v1.8]

- Documentation updates.

7 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols | | | |
|---------------------------|------------|------------------------------|--|
| <code>\!</code> | <u>7</u> | <code>\;</code> | <u>11</u> |
| <code>\"</code> | <u>12</u> | <code>\></code> | <u>13</u> |
| <code>\+</code> | <u>10</u> | <code>\@end</code> | <u>1128</u> |
| <code>\-</code> | <u>9</u> | <code>\@scl</code> | <u>606,</u> |
| <code>\.</code> | <u>365</u> | <code>\@tmp</code> | <u>611, 617, 622, 648, 653, 659, 664</u> |
| <code>\:</code> | <u>8</u> | | <u>539,</u> |
| | | | <u>544, 547, 564, 570, 573, 594,</u> |

| | |
|---------------------------------|---|
| \begin{ | 737, 764, 796, 832, 875, 903, 915, 934, 1021, 1047, 1075, 1094, 1140 |
| \catcode | 7, 8, 9, 10, 11, 12, 13 |
| \chardef | 427, 429, 954, 963, 992 |
| \cmd | 739, 740, 766, 767, 798, 812, 814, 825, 826, 835, 836, 847, 849, 861, 863, 877, 878, 905, 906, 910, 911, 917, 918, 930, 931, 936, 937 |
| \ColModList | 1097, 1113, 1118 |
| \color | 195, 198 |
| \convertcolorspec | 99, 122, 223, 233, 264, 270, 387, 414, 482, 493, 1116, 1121 |
| \csname | 26, 166, 306, 426, 462, 474, 507, 675, 678, 680 |
| \definecolor | 871, 872, 1043, 1044, 1045, 1046 |
| \do | 1113, 1118 |
| \documentclass | 695, 1081, 1132 |
| \end | 762, 793, 830, 867, 901, 912, 932, 944, 1041, 1072, 1076, 1127, 1142 |
| \endcsname | 26, 166, 306, 426, 462, 474, 507, 675, 678, 680 |
| \errhelp | 711, 713, 718, 719 |
| \errmessage | 712, 714, 722, 724 |
| \Errorfalse | 978 |
| \errortest | 773, 782, 783, 784, 806, 817, 818, 819, 829, 841, 852, 853, 854, 855, 866 |
| \Errortrue | 985 |
| \Expect | 731, 740, 767, 799, 814, 826, 836, 849, 863, 878, 906, 911, 918, 931, 937, 958, 959, 960, 967, 968, 969, 972, 983, 984, 996, 997, 998, 1002, 1005 |
| \ExpectError | 709, 774, 785, 807, 820, 842, 856 |
| \extractcolorspec | 121, 251, 413, 492 |
| \fbox | 1136, 1138, 1141 |
| \hbox | 952, 990 |
| \hopatch@AfterPackage | 537 |
| \Hy@pdfversion | 429 |
| \HyColor@{@}{@}{@}UseColor | 192, 197 |
| \HyColor@{@}{@}UseColor | 192, 194 |
| \HyColor@{@}{IfRGB} | 315, 320 |
| \HyColor@{@}UseColor | 187, 191 |
| \HyColor@{@}AttachfileColor | 445, 955, 964, 993 |
| \HyColor@{@}BookmarkColor | 96, 766, 877 |
| \HyColor@{@}CheckDot | 41, 44 |
| \HyColor@{@}CheckNum | 324, 326, 328, 345 |
| \HyColor@{@}DefSanitized | 6, 154, 155, 160 |
| \HyColor@{@}DetectPdfVersion | 424, 466, 478 |
| \HyColor@{@}dot | 344, 355 |
| \HyColor@{@}ModelErrorNoXcolor | 112, 131, 229, 239, 400, 488 |
| \HyColor@{@}ErrorSpecNoXcolor | 126, 138, 277, 418, 499 |
| \HyColor@{@}FieldBColor | 283 |
| \HyColor@{@}FieldColor | 284, 936 |
| \HyColor@{@}HyperrefBorderColor | 384, 835, 847, 861 |
| \HyColor@{@}HyperrefColor | 200, 905, 910 |
| \HyColor@{@}IfModel | 97, 145, 201, 211, 385, 480 |
| \HyColor@{@}{IfRGB} | 247, 304, 409 |

| | |
|-----------------------------|--|
| \HyColor@IfXcolor | 98, 120, 164, 222, 232, 250, 386, 412, 481, 491 |
| \HyColor@MatchNum | 364, 368, 369 |
| \HyColor@model | 99, 103, 106, 133, 135, 154, 159, 202, 212, 214, 217, 219, 221, 223, 226, 233, 236, 252, 254, 257, 260, 263, 264, 268, 270, 273, 285, 292, 294, 296, 335, 370, 387, 391, 394, 458, 465, 477, 482, 510, 518 |
| \HyColor@model@cmyk | 178, 179, 219, 260, 296, 477 |
| \HyColor@model@empty | 172, 173, 212, 510 |
| \HyColor@model@Gray | 180, 181, 221, 263 |
| \HyColor@model@gray | 106, 174, 175, 214, 224, 226, 254, 265, 268, 292, 394, 465 |
| \HyColor@model@rgb | 100, 103, 122, 176, 177, 217, 234, 236, 257, 271, 273, 294, 335, 370, 388, 391, 414, 458, 483, 494 |
| \HyColor@NormalizeCommaCMYK | 86, 220, 261 |
| \HyColor@NormalizeCommaRGB | 78, 101, 104, 123, 218, 235, 248, 258, 272, 389, 392, 410, 415, 484, 495 |
| \HyColor@NormalizeNum | 36, 79, 81, 83, 87, 89, 91, 93, 107, 215, 225, 255, 266, 395, 739 |
| \HyColor@one | 343, 353 |
| \HyColor@PdfVersion | 427, 429, 467, 479, 954, 963, 992 |
| \HyColor@resultfalse | 332, 348, 357, 379, 451 |
| \HyColor@resulttrue | 321, 376 |
| \HyColor@ReverseString | 49, 54, 61, 66 |
| \HyColor@SpaceToComma | 433, 455 |
| \HyColor@StripLeadingZeros | 50, 71, 73 |
| \HyColor@temp | 79, 80, 81, 82, 83, 84, 87, 88, 89, 90, 91, 92, 93, 94, 322, 323, 346, 347, 350, 351, 353, 355 |
| \HyColor@TwoSpaces | 319, 323 |
| \HyColor@UseColor | 182 |
| \HyColor@values | 99, 104, 108, 117, 135, 142, 155, 160, 202, 204, 216, 218, 220, 223, 233, 243, 247, 248, 251, 253, 256, 259, 262, 264, 267, 270, 336, 371, 387, 392, 396, 405, 409, 410, 482 |
| \HyColor@WithModel | 147, 153 |
| \HyColor@WithoutModel | 149, 158 |
| \HyColor@XZeroOneThreeFour | 210, 283, 286, 452, 798, 812, 825, 917, 930 |
| \HyColor@zero | 342, 351 |
| I | |
| \ifdim | 37 |
| \ifError | 975, 983, 1002 |
| \ifHyColor@result | 304, 325, 327, 334, 453 |
| L | |
| \immediate | 707 |
| \in@ | 565, 579 |
| \IncludeTests | 698 |
| \inline | 957, 959, 966, 968, 995, 997 |
| \inlinemacro | 955, 957, 964, 966, 993, 995 |
| M | |
| \makeatletter | 701, 1096, 1135 |
| \makeatother | 1139 |
| \MakeUppercase | 1141 |
| \Message | 706, 707, 725, 726, 727 |
| \MessageBreak | 133, 134, 140, 141, 775, 776, 786, 787, 808, 809, 821, 822, 843, 844, 857, 858, 1012, 1013, 1017, 1018 |
| \ModelNoXcolor | 1011, 1036 |
| N | |
| \NeedsTeXFormat | 2, 534, 1079, 1131 |
| \newcommand | 703, 704, 706, 709, 1097, 1111, 1112 |
| \newif | 304, 975 |
| \NoEmptyModel | 1008, 1032, 1033, 1070, 1071 |
| \nofiles | 1080 |
| O | |
| \OptionName | 877, 917, 930, 936 |
| \OrgPackageError | 979, 987 |
| P | |
| \PackageError | 132, 139, 299, 511, 522, 717, 979, 980 |
| \PackageName | 877, 917, 930, 936 |
| \pdflastmatch | 372, 373, 374 |
| \pdfmatch | 368, 691 |
| \protect | 677 |
| \protected@edef | 1136, 1138 |
| \ProvidesFile | 687, 690, 693 |
| \ProvidesPackage | 3, 535 |
| R | |
| \rangeGray | 622, 664 |
| \rangeHSB | 617, 659 |
| \rangeRGB | 606, 648 |
| \remove@to@nnil | 542, 554, 568, 582 |
| \RequirePackage | 5, 536 |
| \reserved@a | 538, 549, 563, 576, 591, 631 |

| S | |
|-------------------------|--|
| \saved@errhelp | 711, 719 |
| \saved@errmessage | 712, 724 |
| \setbox | 952, 990 |
| \space | 319, 368, 369 |
| \spec | 955, 958, 964, 967, 993, 996 |
| \SpecNoXColor | 1016, 1039, 1040 |
| \StartModel | 1111, 1116, 1117 |
| \StartValues | 1112, 1116, 1117 |
| \strip@prefix | 372, 373, 374 |
| T | |
| \Test | 950, 1022, 1023, 1025, 1027, 1029, 1031, 1048, 1049, 1051, 1053, 1055, 1057, 1058, 1059, 1060, 1061, 1063, 1064, 1066, 1067, 1068 |
| \test | 738, 742, 743, 744, 745, 746, 747, 748, 749, 750, 751, 752, 753, 754, 755, 756, 757, 758, 759, 760, 761, 765, 769, 770, 771, 772, 779, 790, 797, 801, 802, 803, 804, 805, 834, 838, 839, 840, 876, 880, 881, 882, 883, 884, 885, 886, 887, 888, 889, 890, 891, 892, 893, 894, 895, 896, 897, 898, 899, 900, 904, 908, 909, 916, 920, 921, 922, 923, 924, 925, 926, 927, 928, 929, 935, 939, 940, 941, 942, 943 |
| \TestError | 976, 1032, 1033, 1034, 1037, 1039, 1040, 1070, 1071 |
| \TestOptionName | 704, 766, 777, 788, 798, 813, 825, 835, 848, 862, 956, 965, 994, 1009, 1014 |
| \TestPackageName | . 703, 717, 766, 798, 813, 825, 835, 848, 862, 956, 965, 982, 994 |
| \TestTemp | 981, 982 |
| \the | 547, 560, 574, 588, 972, 1005 |
| \tm | 592, 633 |
| U | |
| \usepackage | 697, 733, 734, 870, 1042, 1083, 1084, 1087, 1088, 1089, 1092, 1093, 1133, 1134 |
| W | |
| \wd | 972, 1005 |
| \write | 707 |
| X | |
| \x | 14, 28, 31, 35, 313, 318, 1113, 1114, 1116, 1117, 1121, 1122, 1136, 1138 |
| \XC@calcC | 598, 602, 640, 644 |
| \XC@calcH | 613, 655 |
| \XC@calcM | 607, 612, 618, 623, 649, 654, 660, 665 |
| \XC@calcN | 594, 627, 635, 669 |
| \XC@cnv@gray | 591 |
| \XC@frameb@x | 675, 676, 681 |
| \XC@if@ .. | 551, 556, 559, 578, 584, 587 |
| \XC@ifcase | 563 |
| \XC@ifxcase | 538, 592, 633 |
| \XC@mod@cmy | 597, 639 |
| \XC@mod@cmyk | 601, 643 |
| \XC@mod@Gray | 621, 663 |
| \XC@mod@gray | 638 |
| \XC@mod@HSB | 616, 658 |
| \XC@mod@HTML | 610, 652 |
| \XC@mod@RGB | 605, 647 |
| \XC@mod@rgb | 593, 634 |
| \xx | 1118, 1119, 1121, 1122 |
| Y | |
| \y | 23, 35, 1116, 1117, 1121, 1122 |
| \yy | 1121, 1122 |
| Z | |
| \z@ | 37, 369 |
| \zap@space | 40 |