

Tabulars with reledmac

June 16, 2016

Abstract

This file provides example of using tabular environments with *reledmac*.
We use `edtabularl`, `edtabularc` and `edtabularrr`, with marginal, critical and familiar notes. We also use optional arguments of `\pstart`.

1 Left align

1	linea prima	linea prima	sidenote l, sidenote
2	linea secunda	linea secunda ¹	l
3	linea tertia	linea tertia	
4	linea quarta	linea quarta	
5	linea quinta	linea quinta ¹	
6	linea sexta	linea sexta	

2 Center align

7	linea prima	linea prima	sidenote c, sidenote
8	linea secunda	linea secunda ²	c, sidenote c
9	linea tertia	linea tertia	
10	linea quarta	linea quarta	
11	linea quinta	linea quinta ²	
12	linea sexta	linea sexta	

¹familiar footnote A.

²familiar footnote A.

¹familiar footnote B.

²familiar footnote B.

3 tertia] critical note A

9 tertia] critical note A

4 quarta] critical note B

10 quarta] critical note B

3 Right align

sidenote r, sidenote³
r, sidenote³
15
16
17
18

linea prima
linea secunda³
linea tertia
linea quarta
linea quinta³
linea sexta

linea prima
linea secunda³
linea tertia
linea quarta
linea quinta³
linea sexta

³familiar footnote A.

³familiar footnote B.

15 tertia] critical note A

16 quarta] critical note B