

The eledform extension for eledmac

Maïeul Rouquette
maieul at maieul dot net

v1.1a 2015/08/13

This package is unmaintained. Maïeul Rouquette has no more time to maintain it.

Abstract

The *eledmac* package provides tools to make critical editions of texts. But it doesn't provide any formalism to note the textual variants: each user has to make his own formalism. This package tries to provide a formalism which distinguishes between the *formal* notation of textual variants and their typographical notation¹.

Contents

1	Use	2
1.1	One Example	2
1.1.1	Without formalism	2
1.1.2	With formalism	2
1.2	References	3
1.2.1	Declare the manuscripts	3
1.2.2	Declare variants	3
1.2.3	Customize	3
2	Implementation	4
2.1	Define manuscripts	4
2.2	Print the critical notes	4
2.3	Customization	6
2.3.1	The footnote series	6
2.3.2	Display options	6
2.4	Stemma of the code	6

¹The original idea of this package is described at <http://geekographie.maieul.net/Formaliser-les-variantes>. You can suggest new features or report bugs at <https://github.com/maieul/eledform/issues>.

1 Use

1.1 One Example

1.1.1 Without formalism

Suppose this case :

1. One text, with five manuscripts: P, A, B, C, D. P is the manuscript which is used as reference. Variants in A, B, C, D are shown in the apparatus.
2. The pseudo-word “lorem” has these variants:
 - A and B** the word is omitted.
 - C** the word is replaced by “loram”.
 - D** the word is replaced by “lorim”.

Without formalism, you could write:

```
\edtext{lorem}{\Afootnote{AB \emph{omit}; C loram; D lorim}}
```

Which produces this critical note:

lorem] AB omit; C loram; D lorim

There are some limits for this method:

- If we want to change display, we must change all notes.
- We can't produce statistics.
- Difficulty to export in other format than L^AT_EX.
- No method to check if we're making mistakes regarding to the manuscripts.

1.1.2 With formalism

To describe the same situation, we propose this formalism :

```
\var{lorem}{A,B}{  
  {{C}{loram}},  
  {{D}{lorim}}  
}
```

With *eledform*, this will produce the same result as the non-formalised form, but without the described inconveniences. You can see an example in the file `example.tex`, which produces `example.pdf`.

1.2 References

1.2.1 Declare the manuscripts

`\manuscripts` You have to use `\Manuscripts{<list>}` to provide the list of manuscripts used in the apparatus. L^AT_EX prints a warning message in the log file if you're referring to a manuscript that is not declared before. It also prints an error in the resulting file. The list of manuscripts is a comma separated list:

```
\manuscripts{A,B,C,D}
```

1.2.2 Declare variants

`\var` The main macro is `\var[<short>]{<lemma>}{}{<variants>}[<other>]`. This macro takes five arguments, two are optional.

`<short>` (**optional**) an abbreviated version of the lemma for the notes.

`<lemma>` the lemma which has variants.

`` a comma separated list of manuscripts where the lemma is omitted.

`<variants>` a comma separated list of variants. Each variant has the form `{<manuscripts>}{<variant>}`, where:

`<manuscripts>` a comma separated list of manuscripts where the variant is.

`<variant>` the variant itself.

`<other>` (**optional**) other code linked to the lemma, for example a call to an critical footnote.

1.2.3 Customize

`\manposition` By default (since v1.1), the manuscripts are printed after the variant. With `\manposition{<position>}`, where position is any text except `last`, you can change it.

`\omitposition` By default, the omission are printed at the beginning of the variants. With `\omitposition{<position>}`, where position is any text except `first`, you can change it.

`\varseries` By default, the notes for textual variants are printed in the A series of footnotes. With `\varseries{<letter>}`, you can change it.

`\omittext` When a manuscript omits a lemma, `eledform` prints `\emph{omit}`. You can change it with `\omittext{<text>}`.

`\manvarseparator` By default, a non breakable space is printed between the manuscript letter and the variant. You can change it with `\manvarseparator{<separator>}`.

`\varseparator` By default, a breakable space is printed between each variant of a lemma. You can change it with `\varseparator{<separator>}`.

2 Implementation

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage{eledform}[2015/08/13 v1.1a formalism for eledmac]
3 \RequirePackage{eledmac}
```

2.1 Define manuscripts

`\manuscripts@` The `\manuscripts@` macro is an etoolbox list.

```
4 \def\manuscripts@{}
```

`\manuscripts` The `\manuscripts` macro only fills the `\manuscripts@` macro.

```
5 \newcommand{\manuscript}[1]{%
6   \renewcommand{\do}[1]{\listgadd{\manuscripts@}{##1}}%
7   \docsvlist{#1}%
8 }
```

2.2 Print the critical notes

`\var` The `\var` macro is the only public macro, which calls all private macros.

```
9 \newcommandx*\var}[5][1,5,usedefault]{%
```

First, call the `\edtext` macro.

```
10 \edtext{#2}{%
```

If the `\var` macro is called with the optional first argument, we put it into the `\lemma` macro.

```
11 \ifstrempy{#1}{\lemma{#1}}%
```

The `\varnote@` macro is an Xfootnote macro defined by user, with the `\varnote` macro (cf. 6).

```
12 \varnote@{%
```

In the case where the manuscripts with omission must be printed in first position.

```
13 \ifdefstring{\omitposition@}{first}{
```

```
14 % \end{macrocode}
```

15 % If the third argument is not empty, we call the `\cs{del@}` macro, which print the manuscript where t

```
16 % \begin{macrocode}
```

```
17 \ifstrempy{#3}{}%
```

```
18 {\del@{#3}}%
```

If the third and fourth argument are both not empty, we print the separator between variants.

```
19 \ifstrempy{#4}{%
```

```
20 {}%
```

```
21 {\varseparator@}%
```

```
22 }%
```

And so, we print all the variants which are not an omission.

```
23 \var@{#4}%
```

The same thing, but if the manuscripts with omission must be printed in last position.

```

24         }%
25         {%
26         \ifstrempy{#4}%
27         }%
28         {\var{#4}%
29         \ifstrempy{#3}%
30         }%
31         {\vseparator@}%
32         }%
33         \ifstrempy{#3}{\del@{#3}}%
34         }%
35     }%
36 % \end{macrocode}
37 % Eventually, we add the critical notes which are not for textual criticism.
38 % \begin{macrocode}
39     #5%
40     }%
41 }

```

`\print@manuscript` The `\print@manuscripts` command only prints the manuscripts where a variant exists.

```

42 \newcommand{\print@manuscript}[1]{%
43     \ifinlist{#1}{\manuscripts@}%
44     {#1}%
45     {\eledmac@warning{Manuscript #1 not declared, p.\the\page@num ; l.\the\line@num}\underline{
46     }

```

`\del@` The `\del@` macro prints the manuscripts where the lemma is omitted, and after that, the text to indicate this omission.

```

47 \newcommand{\del@}[1]{%
48     \renewcommand{\do}[1]{%
49         \print@manuscript{##1}%
50     }%
51     \ifdefstring{\manposition@}{last}%
52         {\omittext@\manvseparator@\docsvlist{#1}}%
53         {\docsvlist{#1}\manvseparator@\omittext@}%
54 }

```

`\var@` The `\var@` macro loops on the non omission variants. Except for the first variant, it prints the variant separator.

```

55 \newcommand{\var@}[1]{%
56     \newif\iffirst%
57     \firsttrue%
58     \renewcommand{\do}[1]{\iffirst\firstfalse\else\vseparator@fi{\var@##1}}%
59     \docsvlist{#1}%
60     }

```

`\var@` The `\var@` macro prints manuscripts for a singular variant and this variant after that.

```
61 \newcommand{\var@}[2]{%
62   \renewcommand{\do}[1]{%
63     \print@manuscript{##1}%
64   }%
65   \ifdefstring{\manposition@}{last}%
66     {#2\manvarseparator@\docsvlist{#1}}%
67     {\docsvlist{#1}\manvarseparator@#2}%
68 }
```

2.3 Customization

2.3.1 The footnote series

`\varnote@` The `\varnote@` macro is only a reference to a critical footnote macro of `eledmac`. The default is `\Afootnote`.

```
69 \let\varnote@\Afootnote
```

`\varseries` The `\varseries` macro redefines this reference.

```
70 \newcommand{\varseries}[1]{\letcs{\varnote@}{#1footnote}}
```

2.3.2 Display options

`\new@eledform@custom` The `\new@eledform@custom` macro has two actions :

1. Define the default value of an option (`\option@`).
2. Create the command which modifies this option (`\option`).


```
71 \newcommand{\new@eledform@custom}[2]{%
72   \csgdef{#1@}{#2}%
73   \expandafter\newcommand\csname#1\endcsname[1]{\csgdef{#1@}{##1}}%
74 }
```

And so, we can call `\new@eledform@custom` to define options for user.

```
\omittext
\manvarseparator 75 \new@eledform@custom{omitposition}{first}
\varseparator     76 \new@eledform@custom{manposition}{last}
\manposition      77 \new@eledform@custom{omittext}{\emph{omit}}
\omitposition     78 \new@eledform@custom{manvarseparator}{~}
                  79 \new@eledform@custom{varseparator}{\space}
```

2.4 Stemma of the code

The next figure is a stemma of the code.



Change History

v1.0		the order of the elements.	1
	General: First public release.	1	v1.1a
v1.1	General: News options to change		General: Package unmaintained.
			1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

A	<code>\ifinlist</code>	43	<code>\omittext</code>	<u>75</u>
<code>\Afootnote</code>	<code>\ifstrempy</code>	11, 17, 19, 26, 29, 33	<code>\omittext@</code>	52, 53
B	<code>\begin</code>	16, 38	P	
C	<code>\cs</code>	15	<code>\page@num</code>	45
<code>\csname</code>	<code>\let</code>	69	<code>\print@manuscript</code>	<u>42</u> , 49, 63
	<code>\letcs</code>	70	<code>\ProvidesPackage</code>	2
	<code>\line@num</code>	45	R	
D	<code>\def</code>	4	<code>\renewcommand</code>	6, 48, 58, 62
<code>\del@</code>	<code>\manposition</code>	<u>75</u>	<code>\RequirePackage</code>	3
<code>\do</code>	<code>\manposition@</code>	51, 65	S	
<code>\docsvlist</code>	<code>\manuscript</code>	5	<code>\space</code>	79
52, 53, 59, 66, 67	<code>\manuscripts</code>	<u>5</u>	T	
E	<code>\manuscripts@</code>	<u>4</u> , 6, 43	<code>\the</code>	45
<code>\edtext</code>	<code>\manvarseparator</code>	<u>75</u>	U	
<code>\eledmac@warning</code>	<code>\manvarseparator@</code>	52, 53, 66, 67	<code>\underline</code>	45
<code>\emph</code>	N		V	
<code>\end</code>	<code>\NeedsTeXFormat</code>	1	<code>\var</code>	<u>9</u>
<code>\endcsname</code>	<code>\new@eledform@custom</code>	<u>71</u> , 75–79	<code>\var@</code>	23, 28, <u>55</u>
<code>\expandafter</code>	<code>\newcommand</code> 5, 42, 47, 55, 61, 70, 71, 73		<code>\var@@</code>	58, <u>61</u>
F	<code>\newcommandx</code>	9	<code>\varnote@</code>	12, <u>69</u> , 70
<code>\firstfalse</code>	<code>\newif</code>	56	<code>\varseparator</code>	<u>75</u>
<code>\firsttrue</code>			<code>\varseparator@</code> 21, 31, 58	
I	O		<code>\varseries</code>	<u>70</u>
<code>\ifdefstring</code> 13, 51, 65	<code>\omitposition</code>	<u>75</u>		
<code>\iffirst</code>	<code>\omitposition@</code>	13		